Plugging of well Log #105908

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 111 109
Permit No. —
Basin 054

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60676

1 OWNER Trail Mountain / Yates Petroleum Group
MAILING ADDRESS P.O. Box 1908
Rock Springs, WY 82902

ADDRESS AT WELL LOCATION Crescent Valley / Palisades #1
Subdivision Name: County: Eureka

2 LOCATION SE ¼ SW ¼ Sec 27 T 31N N/S R 51 E
PERMIT/WAIVER No. OG 246 Issued by Water Resources Parcel No.

Latitude 40. 32. 197 N
Longitude 116. 12. 916 W
UTM E N NAD 83
☐ NAD 27 ☒ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? yes
If yes, what is NDWR well log #? 105908

4 EXISTING WELL CONSTRUCTION
Depth Drilled 205 Feet Depth Cased 205 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"	12.92	188	+2	205
8"	16.94	188	+1	160

Existing Perforations:
Type of perforation Mill Slot
Size of perforation 3/16" x 3"
From 185 feet to 205 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

5 WATER LEVEL
Static water level 25 feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature °F Quality

6 Additional Notes or Comments

6" casing was pulled back to 20'
Bentonite was placed in bottom of hole
6" casing was removed. Concrete was poured in 8" casing to surface.
8" casing was removed & concrete topped off hole.

NAD-27 GPS
N 40.536727
W 116.214398

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☒ yes ☐ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used:
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used		
0	185		Concrete	☐ Pumped	☒ Poured
185	205		3/4 Kiwik Plug	☐ Pumped	☒ Poured
				☐ Pumped	☐ Poured
				☐ Pumped	☐ Poured
				☐ Pumped	☐ Poured
				☐ Pumped	☐ Poured

Neat Cement Fluid Weight lbs/gal
Bentonite Grout % bentonite
Date Started 10-Jun-10
Date Completed June 10. 2010

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Sharel C. Fertig Sr., dba Fertig Drilling Company (Contractor)
Address P.O. Box 525 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board ~~061904~~ 0031904
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1584
Signed (By driller performing actual drilling on site or contractor)
Date 6-22-10

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

PLO