Replacement Well, (Original Well Log 25199, Reconditioned Log 97659)

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 111141
Permit No. 49298
Basin 205

NOTICE OF INTENT NO. 34795

1. OWNER EWING INVESTMENTS
MAILING ADDRESS 1200 A ST.
LAS VEGAS, NV. 89106-3215

ADDRESS AT WELL LOCATION 1625 STATE HYWAY 168, MOAPA, NV.

2. LOCATION NW 1/4 NW 1/4 Sec. 2 T. 15 ☐/S R 66 E. CLARK County
PERMIT NO. 49298 Issued by Water Resources | 042-02-101 Parcel No. | 0084-088 Subdivision Name

3. WORK PERFORMED
☐ New Well ☑ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Gravel		0	12	
Boulders		12	20	
Sand + Gravel + Water		20	40	
Cemented Gravel		40	50	
Gravel + Boulders Water		50	100	
Sandstone		100	65	
Shale		65	90	
Clay + Sand		90	150	
Sandstone		150	280	
Clay		280	305	
Sandstone		305	405	
Clay + Gravel		450	480	
Sandstone		480	600	

☒ NAD-27 GPS ~~36.581694° N 114.583096° W~~
36.6658333 114.5839166
N 36° 34' 54.8
W 114° 35' 02.1 ← GPS coordinates supplied by driller inaccurate.
Drove Casing to 105 ft
Shut all water off
Based upon APN, I corrected GPS location
Drilled on to 600 ft
No water
Back filled Cement
Then Perforated with air Perforator
088

Date started 02-16-10, 20
Date completed 03-23-10, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Drawdown (Feet)	Time (Hours)

RECEIVED APR 20 2010 LAS VEGAS OFFICE

8. WELL CONSTRUCTION
Depth Drilled 105 Feet Depth Cased 105 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12 1/4 Inches		0 Feet	105 Feet
7 7/8 Inches		105 Feet	600 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	16.9	.188	+5	105
Back Filled 7 7/8 Hole with Neat Cement				

Perforations:
Type perforation AIR PERFORATOR
Size perforation 3/16 x 4 Times Around
From 50 feet to 100 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☑ No
From feet to feet

9. WATER LEVEL
Static water level 12 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 60.1 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name VERNON H. DIMICK
Contractor
Address 5740 Tee Pee Ln
Contractor
LV. NV. 89149
Nevada contractor's license number issued by the State Contractor's Board 10062
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 552
Signed V H Dimick
By driller performing actual drilling on site or contractor
Date 04-08-10

PLD, F

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627