STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 111156
Permit No. —
Basin 03DA

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. #64418

1 OWNER KINGS RIVER RANCH
MAILING ADDRESS 129 KINGS RIVER RD
OROVADA, NV. 89425

ADDRESS AT WELL LOCATION KINGS RIVER RANCH
129 KINGS RIVER RD OROVADA, NV 89425
Subdivision Name: BRINKERHOFF WELL County: HUMBOLDT

2 LOCATION NW¼ SE ¼ Sec 22 T 46 N/S R 33 E
PERMIT/WAIVER No. UNKNOWN Issued by Water Resources Parcel No.

Latitude N 41° 51' 06.9" UTM E
Longitude W 118° 15' 08.0" N
☐ NAD 27 ☒ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?

Is there an existing well log? UNKNOWN
If yes, what is NDWR well log #? None Found.

4 EXISTING WELL CONSTRUCTION
Depth Drilled 380 Feet Depth Cased 380 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
30'		3/8 - 0.375	0	100
18'		5/16 - 0.312	0	380

Existing Perforations:
Type of perforation JOHNSON WELL SCREEN
Size of perforation
From 180 feet to 380 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

5 WATER LEVEL
Static water level 102 feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature °F Quality

6 Additional Notes or Comments
328- BAGS TC BENTONITE GROUT 380' - 60'

12- BAGS VOLCLAY CHIPS 60' - 50'

52-BAGS CEMENT AT 7 GALS WATER/BAG

WE HAD SOME OTHER PROJECTS GOING AT THE SAME TIME. WE TOOK TIME TO LET THE MUD SETTLE ON ITS OWN

THE OPERATION WENT QUIT WELL

STATE ENGINEERS OFFICE
2010 JUL -1 AM 11:18

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used: MILLS KNIFE
From 180 feet to 3 feet Number of perfs per linear foot 4
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot

8 WELL PLUGGING MATERIALS

				Material Used		
From 380	feet to	60	feet	BENTONITE	☒ Pumped	☐ Poured
From	feet to		feet		☐ Pumped	☐ Poured
From 60	feet to	50	feet	BEN- CHIPS	☐ Pumped	☒ Poured
From	feet to		feet		☐ Pumped	☐ Poured
From 50	feet to	2	feet	CEMENT	☐ Pumped	☒ Poured
From	feet to		feet		☐ Pumped	☐ Poured

Neat Cement Fluid Weight lbs/gal 12.4 - 12.6
Bentonite Grout % bentonite 30%
Date Started FEB 18 2010
Date Completed JUNE 11 2010

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name KINGS RIVER RANCH Contractor
Address 129 KINGS RIVER ROAD Contractor
OROVADA, NV. 89425
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1712
Signed Mike McDonald By driller performing actual drilling on site or contractor
Date June 25 2010

(Rev. 05-06) NAD 27 GPS
41.852020°N
118.251231°W

USE ADDITIONAL SHEETS IF NECESSARY

PLO.