STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 111 182
Permit No. —
Basin 044

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65992

1. OWNER YUKON-NEVADA GOLD CORP
MAILING ADDRESS HC 31, BOX 78
ELKO, NV 89801

ADDRESS AT WELL LOCATION JERRITT CANYON MILL SITE
TAILINGS POND ***HOLE #GW-66***
Subdivision Name: PARCEL OF LAND County: ELKO

2. LOCATION SW ¼ NW ¼ Sec 3 T 40N N/S R 54 E
PERMIT/WAIVER No. NDP # NVE 00020 (Issued by Water Resources) 005-570-007 Parcel No.

Latitude 41.393580758
Longitude 115.886462261
UTM E
N
[X] NAD 27
[ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND & GRAVEL		0	20	20
CLAY & SAND w/FINE GRAVEL		20	30	10
FINE GRAVEL & SAND & SILT		30	60	30
SAND & GRAVEL		60	80	20
GRAVEL w/SAND & CLAY		80	90	10
SAND & CLAY w/FINE GRAVEL		90	140	50
MED GRAVEL w/SAND	X	140	180	40
1st WATER @ 160'				
CASING INSTALLED WITH				
PLASTIC CAP ON TOP &				
BOTTOM				
141' TO 143' BENTONITE				
PELLETS PLACED				
6" X 7' STEEL CASING				
MONUMENT w/LOCKING CAP				
INSTALLED IN A 3' x 3' x 6"				
CONCRETE PAD				

Date started: 14-Jun, 20 10
Date completed: 15-Jun, 20 10

9. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 179 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
7 7/8	Inches	0	Feet	180	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sch 40 Monoflex thread	+1	179
6.625	13	.188	+2	5

Perforations:
Type of perforation FACTORY PERFORATED PLASTIC
Size of perforation 0.020 SLOT
From 149 feet to 179 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 0 to 10 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[X] ≥30% Bentonite Grout 15 to 141 [X] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 143 to 180 [ ] Pumped [X] Poured
Type: 3/8" WASH PEA GRAVEL
Bentonite Chips: [X] Yes [ ] No 10 to 15 [ ] Pumped [X] Poured
Type: 3/8" BENTONITE CHIPS

7. Water Level
Static water level: 128 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 56 °F
Quality: POOR

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
125 PSI @	4		1.25
825 CFM			

STATE ENGINEER'S OFFICE
2010 JUL -9 PM 1:27
RECEIVED

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC. (Contractor)
Address P. O. BOX 850 (Contractor)
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1653
Signed (By driller performing actual drilling on site or contractor)
Date 6/24/2010

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY
PLO. F