

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 111.185
Permit No. _____
Basin 044

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65995

1. OWNER YUKON-NEVADA GOLD CORP
MAILING ADDRESS HC 31, BOX 78
ELKO, NV 89801

ADDRESS AT WELL LOCATION JERRITT CANYON MILL SITE
TAILINGS POND ***HOLE #GW-69***
Subdivision Name: PARCEL OF LAND County: ELKO

2. LOCATION SE 1/4 NW 1/4 Sec 4 T 40N N/S R 54 E
PERMIT/WAIVER No. NDP # NVE 00020 005-570-007
Issued by Water Resources Parcel No.

Latitude 41.393193346 UTM E NAD 27
Longitude 115.899813481 N NAD 83/WGS 84

3. WORKED PERFORMED
 New Well Replace Recondition
 Deepen Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG				
Material	Water Strata	From	To	Thick-ness
GRAVEL & BOULDERS		0	10	10
SAND & CLAY		10	35	25
GRAVEL		35	40	5
GRAVEL w/ SAND & CLAY		40	80	40
GRAVEL & SAND		80	110	30
GRAVEL w/ SAND & CLAY	X	110	140	30
1st WATER @ 120'				
CASING INSTALLED WITH PLASTIC CAP ON TOP & BOTTOM				
112' TO 114' BENTONITE PELLETS PLACED				
6" X 7' STEEL CASING MONUMENT w/LOCKING CAP INSTALLED IN A 3' x 3' x 6" CONCRETE PAD				

9. WELL CONSTRUCTION					
Depth Drilled	140	Feet	Depth Cased	139	Feet
HOLE DIAMETER (BIT SIZE)					
	From		To		
10 5/8	Inches	0	Feet	10	Feet
7 7/8	Inches	10	Feet	140	Feet
	Inches		Feet		Feet

CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sch 40 Monoflex thread	+1	139
6.625	13	.188	+2	5

Perforations:
Type of perforation FACTORY PERFORATED PLASTIC
Size of perforation 0.020 SLOT
From 119 feet to 139 feet
From _____ feet to _____ feet
From _____ feet to _____ feet
From _____ feet to _____ feet

Annular Seal: Yes No
 Neat Cement 0 to 10 Pumped Poured
 Cement Grout _____ to _____ Pumped Poured
 Concrete Grout _____ to _____ Pumped Poured
 ≥30% Bentonite Grout 20 to 112 Pumped Poured
Gravel Pack: Yes No 114 to 140 Pumped Poured
Type: 3/8" WASH PEA GRAVEL
Bentonite Chips: Yes No 10 to 20 Pumped Poured
Type: 3/8" BENTONITE CHIPS

Date started: 18-Jun, 20 10
Date completed: 18-Jun, 20 10

7. Water Level
Static water level: 101 feet below land surface
Artesian Flow: _____ G.P.M. _____ P.S.I.
Water Temperature: 58 °F
Quality: POOR

8. WELL TEST DATA			
TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailor <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift			
125 PSI @ 825 CFM	2		

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC.
Contractor
Address P. O. BOX 850
Contractor
ELKO, NV 89803
Nevada contractor's license number _____
issued by the State Contractor's Board 020582
Nevada driller's license number issued by the _____
Division of Water Resources, the on-site driller 1653
Signed [Signature]
By driller performing actual drilling on site or contractor
Date 6/24/2010