STATE OF NEVADA
DIVISION OF WATER RESOURCES
# WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 111240
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 32469

1. OWNER U-HAUL REALSTATE COMPANY
MAILING ADDRESS P.O. BOX 29046 PHOENIX AZ. 85038
ADDRESS AT WELL LOCATION 2021 W. BONANZA LAS VEGAS NV.
Subdivision Name: County: CLARK

2. LOCATION SW ¼ SW ¼ Sec 28 T 20 N/S R 61 E
PERMIT/WAIVER No. 1392840023
Issued by Water Resources Parcel No.
Latitude 36° 10 36 99"
Longitude 115° 10 06 05"
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| ASPHALT | | 0 | .25 | .25 |
| SAND + STONE FILL | | .25 | 1.0 | .75 |
| SILT SAND & GRAVEL | | 1.0 | 8.0 | 7.0 |
| CALCHE | | 8.0 | 10.0 | 2.0 |
| MOIST CALCHE | | 10.0 | 16.5 | 6.5 |
| MOIST CLAY + CALCHE | YES | 16.5 | 20.0 | 13.5 |

RECEIVED FEB 05 2010 LAS VEGAS REGION

FACILITY ID. NO.
8-000708
AS-2

Date started: 2 - 2 , 20 10
Date completed: 2 - 2 , 20 10

7. Water Level
Static water level: 18.5' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | |

9. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | | To | |
|---|---|---|---|---|---|
| 8 | Inches | 0 | Feet | 30 | Feet |
| | Inches | | Feet | | Feet |
| | Inches | | Feet | | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 2 | | SCH 40 | 0 | 30 |
| | | | | |

Perforations:
Type of perforation MACHINE SLOT
Size of perforation .020
From 25 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No

| | | | | |
|---|---|---|---|---|
| ☐ Neat Cement | to | | ☐ Pumped | ☐ Poured |
| ☐ Cement Grout | 1 to 22 | | ☐ Pumped | ☒ Poured |
| ☐ Concrete Grout | 0 to 1 | | ☐ Pumped | ☒ Poured |
| ☐ ≥30% Bentonite Grout | to | | ☐ Pumped | ☐ Poured |

Gravel Pack: ☒ Yes ☐ No 24 to 30 ☐ Pumped ☒ Poured
Type: #3
Bentonite Chips: ☒ Yes ☐ No 22 to 24 ☐ Pumped ☒ Poured
Type: 3/8"

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name EAGLE DRILLING
Contractor
Address 7150 PLACID ST.
Contractor
LAS VEGAS NV 89119
Nevada contractor's license number issued by the State Contractor's Board 51266
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2357
Signed Mike L Wilkins
By driller performing actual drilling on-site or contractor
Date 2 - 3 - 2010

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

(NSPO 3-08)

(O) 627