STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 111 256
Permit No. —
Basin 039

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65696

1. OWNER Ruggeri Stocks LLC
MAILING ADDRESS Box 260091, Jarbidge, NV 89826
ADDRESS AT WELL LOCATION Jarbidge, NV
Subdivision Name: County: Elko

2. LOCATION SW ¼ NE ¼ Sec 21 T 46N N/S R 58 E
PERMIT/WAIVER No. NEV~~209112~~ → 2009112
Issued by Water Resources Parcel No.
Latitude W 115*25.115 UTM E [X] NAD 27
Longitude N 41*51.740 N [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
gray granite		0	40	40
red granite		40	60	20
white ash		60	120	60
gray granite		120	190	70
hard gray granite		190	220	30
dark gray granite		220	226	6
gray granite		226	250	24
betonite pellets 235-238				
pure gold grout 10-235				
neat cement 0-10				
3/3 cement pad 8" monument				
+2 1/2 to 5				
NAD 27 GPS				
41.862333°N				
115.418583°W				

Date started: 11-Jul, 20 10
Date completed: 13-Jul, 20 10

7. Water Level
Static water level: dry feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
dry		2

9. WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8 1/4	Inches	0	Feet	250	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4		sch 80	+2 1/2	250

Perforations:
Type of perforation millslot
Size of perforation .020
From 240 feet to 250 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 0 to 10 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[X] ≥30% Bentonite Grout 10 to 235 [X] Pumped [ ] Poured
Gravel Pack: [X] Yes [ ] No 238 to 250 [ ] Pumped [X] Poured
Type: silica sand 10-20
Bentonite Chips: [X] Yes [ ] No 235 to 238 [ ] Pumped [X] Poured
Type: 1/4 pellets

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Alternative Drilling (Contractor)
Address P.O. Box 281166 (Contractor)
Lamoille, NV 89828
Nevada contractor's license number issued by the *State Contractor's Board* 73955
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1689
Signed (By driller performing actual drilling on site or contractor)
Date 7-13-2010

STATE ENGINEER'S OFFICE 2010 JUL 19 AM 11:45 RECEIVED

(Rev. 05-09) USE ADDITIONAL SHEETS IF NECESSARY

PLD.