

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 111336
Permit No. 69184
Basin 083

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65902

1 OWNER Canyon General Improvement District
MAILING ADDRESS 400 Canyon Way
Sparks, NV. 89434

ADDRESS AT WELL LOCATION At the end of Ave. De La Coulers
at the water treatment plant in Lockwood

Subdivision Name: _____ County: Storey

2 LOCATION NW 1/4 SE 1/4 Sec 16 T 19N N/S R 21 E
PERMIT/WAIVER No. _____

Latitude 39 51096N UTM E NAD 27
Longitude 119 63472W N NAD 83/WGS 84

issued by Water Resources Parcel No. _____

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? no

Is there an existing well log? maybe

If yes, what is replacement well NOI? _____

If yes, what is NDWR well log #? 11040?

4 EXISTING WELL CONSTRUCTION

Depth Drilled 165 Feet Depth Cased 130 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>8</u>		<u>.188</u>	<u>+2</u>	<u>130'</u>

7 WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? yes no

If well was not cleaned out to total depth, please explain why: Casing ended at 130' and since well was measured at 162', we did not want to collapse the bottom of the borehole

Existing Perforations:

Type of perforation	From	To
<u>torch cut</u>	<u>90'</u>	<u>130'</u>

Was the well contaminated? yes no

Was the casing pulled? yes no

Was the casing over drilled? yes no

If casing was left in place, please show where additional perforations were made:
Additional Perforations: _____

Type of perforator used: Mills Knife

From	To	Number of perfs per linear foot
<u>90'</u>	<u>surface</u>	<u>4</u>

5 WATER LEVEL

Static water level 36.3' feet below land surface

Artesian flow _____ G.P.M. _____ P.S.I.

Water temperature _____ °F Quality _____

8 WELL PLUGGING MATERIALS

From	To	Material Used	Quantity
<u>5'</u>	<u>162'</u>	<u>neat cement</u>	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments

Measured static water level at 36.3' and depth of well at 162'
Installed Mills Knife to 90' and cut 4 rows per foot from 90' to surface. We then installed 2" tremmie pipe to 157' and pumped in 4 yards of neat cement from bottom of well to surface. Actual well volume should have required 2.1 cubic yards.

NAD-27 GPS -
39.510960 °N
119.634720 °W

Plugging of Well Log 11040

STATE ENGINEERS OFFICE
2010 JUL 28 AM 11:56

Neat Cement Fluid Weight 14.5 lbs/gal

Bentonite Grout _____ % bentonite

Date Started 7/22/2010

Date Completed 7/23/2010

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Carson Pump, LLC
Contractor

Address P.O. Box 20159
Contractor

Carson City, NV. 89721

Nevada contractor's license number issued by the State Contractor's Board 39920A

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2265

Signed [Signature]
By other performing actual drilling on site or contractor

Date 7/26/2010