

**STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT**

**OFFICE USE ONLY**  
Log No. 111391  
Permit No. \_\_\_\_\_  
Basin 087

**PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 64101

1 OWNER Chris Dianda  
MAILING ADDRESS 1050 South 21st St.  
Sparks, NV 89431

ADDRESS AT WELL LOCATION 8525 Bellhaven Rd.  
Reno, NV 89511  
Subdivision Name: \_\_\_\_\_ County: Washoe

2 LOCATION NE ¼ NW ¼ Sec 11 T 18N N/S R 19 E  
PERMIT/WAIVER No. 041-130-02  
Issued by Water Resources Parcel No.

Latitude 39.44496 UTM E  NAD 27  
Longitude 119.81878 N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? yes  
If yes, what is replacement well NOI? 64101  
Is there an existing well log? yes  
If yes, what is NDWR well log #? 5358

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 113 Feet Depth Cased 100 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.97	.188	-2	100

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

Existing Perforations:

Type of perforation	Size of perforation	From	To
Mills Knife	1/4 x 2	50 feet	80 feet
		90 feet	95 feet

Additional Perforations:

Type of perforator used:	From	To	Number of perfs per linear foot
Mills Knife	0 feet	100 feet	4

5 WATER LEVEL  
Static water level 98 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature cold °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

6 Additional Notes or Comments

12 bags grout  
35 bags neat cement

From	To	Material Used	Pumped	Poured
0	27	neat cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
27	113	Bentonite grout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>

Neat Cement Fluid Weight 15.5 lbs/gal  
Bentonite Grout 20 % bentonite  
Date Started 3/16/2009  
Date Completed 3/16/2009

39.445, 049°N NAD27 D.D.  
119.817, 757°W

See replacement well log #110412  
(drilled under same NOI)

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name McKay Drilling Inc. Contractor  
Address 4850 Joule St #A5 Contractor  
Reno, NV 89502  
Nevada contractor's license number issued by the State Contractor's Board 14170  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2121  
Signed Steve McKay  
By driller performing actual drilling on site or contractor  
Date 3/18/2009

03-1 111 03 2009 0002

USE ADDITIONAL SHEETS IF NECESSARY

MMH-Ⓟ