STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT
CORRECTED

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

OFFICE USE ONLY
Log No. 111396
Permit No.
Basin 048

NOTICE OF INTENT NO. 65053 (1)

1. OWNER Quintin & Malinda Perkins
MAILING ADDRESS 288 Emmigrant Trail #10
Spring Creek, NV 89815

ADDRESS AT WELL LOCATION Dusty Trails
Elevation 5280
Subdivision Name: County: Elko

2. LOCATION SE ¼ SW ¼ Sec 25 T 33N N/S R 55 E
PERMIT/WAIVER No. 077-006-025
Issued by Water Resources Parcel No.

Latitude 40° 42.635 N
Longitude 115° 43.830 W
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown Clay Loam		0	42	42
Soft Sandstone		42	48	6
Hard Sandstone		48	62	14
Soft Sandstone	X	62	65	3
Hard Sandstone		65	87	22
Soft Sandstone	X	87	90	3
Hard Sandstone		90	130	40

40.710,659°N NAD27 D.D.
115.729,602°W

Date started: April 5, , 20 10
Date completed: 6-Apr , 20 10

RECEIVED 2010 JUN 24 AM 10:43 STATE ENGINEER

9. WELL CONSTRUCTION
Depth Drilled 130 Feet Depth Cased 127 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 1/2	Inches	0	Feet	130	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.92	.188	+1	28
6	PVC	SDR-17	28	127

Perforations:
Type of perforation Screan
Size of perforation .032
From 107 feet to 127 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 28 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 52 to 127 ☐ Pumped ☒ Poured
Type: 3/8 pea gravel
Bentonite Chips: ☒ Yes ☐ No 28 to 52 ☐ Pumped ☒ Poured
Type: 3/8 Kiwk Plug

7. Water Level
Static water level: 60 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cold °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Approx	45		2.5

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Sharel C. Fertig Sr., dba Fertig Drilling Company (Contractor)
Address P.O. Box 525 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 031904
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1584
Signed (By driller performing actual drilling on-site or contractor)
Date 6-21-10

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY

* original/duplicate log received 6/1/2010
- signed by driller 5/25/2010

MMH-(F)