

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 111452  
Permit No. 59249  
Basin 064

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65949

1 OWNER Newmont Mining Corp.  
MAILING ADDRESS 1655 Mountain City Hwy  
EIKO, NV. 89801

ADDRESS AT WELL LOCATION Love Tree Mine  
Subdivision Name: \_\_\_\_\_ County: Humboldt

2 LOCATION N 1/4 NW 1/4 Sec 13 T 34 NSR 42 E  
PERMIT/WAIVER NO. 59249 Parcel No. N/A

Latitude \_\_\_\_\_ UTM E 482765  NAD 27  
Longitude \_\_\_\_\_ N 4519379  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? NO  
If yes, what is replacement well NOI? \_\_\_\_\_  
Is there an existing well log? YES  
If yes, what is NDWR well log #? 97128

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 1489 Feet Depth Cased 1480 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
32.5	176.88	0.5"	5	50
24	94.62	0.375"	5	1480

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

Existing Perforations:  
Type of perforation Lower  
Size of perforation 0.125"  
From 946 feet to 1080 feet  
From 1320 feet to 1480 feet

If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used: STAR  
From 50 feet to 940 feet Number of perfs per linear foot 4 X 12 INCHES  
From 1080 feet to 1320 feet Number of perfs per linear foot 4 X 12 INCHES

5 WATER LEVEL  
Static water level 93 FT. feet below land surface  
Artesian flow N/A G.P.M. N/A P.S.  
Water temperature \_\_\_\_\_ °F Quality Good

8 WELL PLUGGING MATERIALS  
Material Used  
From 1480 feet to 810 feet Super Plug  Pumped  Poured  
From 40 feet to 20 feet 3/4" Best Chipp  Pumped  Poured  
From 20 feet to 0 feet Neat Cement  Pumped  Poured

6 Additional Notes or Comments  
Trap to bottom All Clear  
Put on 24" Penetrator. Perforate casing in intervals as recorded above.  
Even tapping into bottom. Pump 1400 Bags of Super Plug. 54400 gal Slurry.  
Abandonment Level @ 3 FT. Settle to 40 FT.  
Pump in 7 FT<sup>3</sup> of 3/4" hole plug.  
Bentonite Chipp. Bring level up to 20 FT.  
Pump in 460 gal of neat cement to top.  
(50 bag of Port Land Cement).  
  
NAD 27 GPS 40.827160°N  
117.204392°W  
  
Plugging of Well Log 97128  
  
Permit 59249

Neat Cement Fluid Weight 16 lbs/gal  
Bentonite Grout 12.1% bentonite  
Date Started 7-22-10  
Date Completed \_\_\_\_\_

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Beart Longyear Nevada Contractor  
Address PO Box 2748 EIKO, NV. 89803 Contractor  
Nevada contractor's license number \_\_\_\_\_  
issued by the State Contractor's Board 0073086  
Nevada driller's license number issued by the \_\_\_\_\_  
Division of Water Resources, the on-site driller 2260  
Signed [Signature]  
By Driller performing actual drilling on site or contractor  
Date 7-26-10

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
2010 AUG - 0 11 10 10

USE ADDITIONAL SHEETS IF NECESSARY