WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 111666
Permit No.
Basin 071

NOTICE OF INTENT NO. 64790 (i)

1. OWNER Richard Andrews
MAILING ADDRESS 3150 Potbelly Rd. Winnemucca NV. 89445
ADDRESS AT WELL LOCATION 3150 Potbelly Rd. Winnemucca NV.

2. LOCATION SE ¼ NE ¼ Sec. 25 T. 35 N/S R. 37 E. Humboldt County
PERMIT NO. (Issued by Water Resources) Parcel No. 01414301 Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
■ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
■ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ■ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
gravel + boulders Sand	yes	140	240	100
GPS				
N 40° 52.885				
W 117° 45.644				
NAD 83				
WGS 84				
40.881513 °N	NAD27	D.D.		
117.759770 °W		-GPS-		
deepens well log #	14114			

Date started 8-5, 2010
Date completed 8-10, 2010

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25	0	5

8. WELL CONSTRUCTION
Depth Drilled 140 to 240 Feet Depth Cased 180 to 240 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 Inches	140 Feet	240 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.25	~~Sched 40~~ PVC	Sched 40	120	240

Perforations:
Type perforation slot
Size perforation .25 x 4"
From 180 feet to 240 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal NA
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 140 feet to 240 feet

9. WATER LEVEL
Static water level 120' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Firstgold Corp. (Contractor)
Address P.O. Box C (Contractor)
Lovelock NV. 89419
Nevada contractor's license number issued by the State Contractor's Board 71020
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 730
Signed Gerald Mosty (By driller performing actual drilling on site or contractor)
Date 8-16-10

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY MMH-(F) (O)-627