

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 112234
Permit No.
Basin $\phi 36$

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1 OWNER Yukon Nevada Gold Corp.
MAILING ADDRESS HC-31 Box 78 ELKO, NV. 89801

ADDRESS AT WELL LOCATION Jeritt Canyon Mine
Murray
Subdivision Name: County: Elko

NOTICE OF INTENT NO. 65014

2 LOCATION NE NE 1/4 Sec 30 T 40 N R 53 E
PERMIT/WAIVER No.

Latitude 41.2354, 48.105 UTM E 584715.29 NAD 27
Longitude 115.5911, 79.106 N 4583275.08 NAD 83/WGS 84

3 Inject ion well TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?
Is there an existing well log? yes
If yes, what is NDWR well log #? 67326

4 EXISTING WELL CONSTRUCTION
Depth Drilled 1300' Feet Depth Cased 1300' Feet
EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4	11.35	.250	0	1300

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:

Type of perforation	Size of perforation	From	To
Vert. Slot	125	1300'	640'

Additional Perforations:
Type of perforator used: Air

From	To	Number of perfs per linear foot
430'	900'	12

5 WATER LEVEL
Static water level 493' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature ° F Quality

8 WELL PLUGGING MATERIALS
Material Used Neat Cement 5 yards

From	To	Material	Pumped	Poured
1300'	0'	Neat Cement	<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments
Ran 3" O.D. pipe in well and clean well to 1300' - Lots of dirt. Trip out and put on perforator. Re-enter and perf. 430' to 900' - Double Pass. Trip and take perforator off. Re-enter to 1300' - Run & pump 5 yards of thick neat cement in lifts up to surface.

Neat Cement Fluid Weight Thick lbs/gal
Bentonite Grout % bentonite
Date Started 10-9-10
Date Completed 10-10-10

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Ward Weaver Rimrock Drilling
Address 2305 Last Chance Rd. ELKO, NV. 89801
Nevada contractor's license number issued by the State Contractor's Board 0030630
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676
Signed Ward Weaver
Date 10-16-10

By driller performing actual drilling on-site or contractor