

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 112236
Permit No. 044
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65017

1 OWNER Yukon Nevada Gold Corp.
MAILING ADDRESS HC 37 Box 78 ELKO, NV.
89801

ADDRESS AT WELL LOCATION Territt Canyon Mine
East Dash
Subdivision Name: County:

2 LOCATION SE 1/4 NW 1/4 Sec 17 T 40 S R 54 E
PERMIT/WAIVER No. M/O -1321
Issued by Water Resources Parcel No.

Latitude 412133.84470 UTM E 590213.73 NAD 27
Longitude 115.5517.33218 N 4579003.84 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a
replacement well was drilled? NO
If yes, what is replacement well NCI?

Is there an existing well log? yes
If yes, what is NDWR well log #? 94834

4 EXISTING WELL CONSTRUCTION
Depth Drilled 1360 Feet Depth Cased 1347 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1 7/8	.7	0.2480 PK	0	1347

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:
Type of perforation Horiz slot
Size of perforation .080
From 1347 feet to 454 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used:
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot

5 WATER LEVEL
Static water level 480 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From 1345	feet to	0	Neat Cement 2 yard plus	<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments
Rig up on monitor well - Run
Trim to 1345 - Hook up to head on
Drill Pipe. Turn on Air & Clean.
1347 - 1340 cased in when Drill Pipe
was tripped out - Oct 2004.
Mix & pump Neat cement in lifts
1345 up to surface. Little over
2 yards Neat Cement.

Neat Cement Fluid Weight Thick lbs/gal
Bentonite Grout % bentonite
Date Started 9-23-10
Date Completed 9-23-10

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true
to the best of my knowledge.
Name Ward Weaver Rimrock Drilling Contractor
Address 2305 Last Chance Rd. ELKO, NV, 89801 Contractor
Nevada contractor's license number issued by the State Contractor's Board 0030630
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676
Signed Ward Weaver By driller performing actual drilling on-site or contractor
Date 10-16-10