

I W-9

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 112237
Permit No. 444
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65007

1 OWNER Yukon Nevada Gold Corp.
MAILING ADDRESS HC-31 Box 78 ELDON, NV. 89801

ADDRESS AT WELL LOCATION Jerritt Canyon Mine
East DASH
Subdivision Name: County:

2 LOCATION NE 1/4 NW 1/4 Sec 17 T 40 S R 54 E
PERMIT/WAIVER No. Issued by Water Resources Parcel No. 1155508.14353

Latitude 412150.31427 UTM E 690420.89 NAD 27
Longitude 4579514.39 NAD 83/WGS 84

3 TYPE OF WELL
 Injection Well X
 Domestic
 Municipal/Industrial
 Irrigation
 Monitor
 Test
 Stock

Is this well being plugged because a replacement well was drilled? N
If yes, what is replacement well NOI?

Is there an existing well log? yes
If yes, what is NDWR well log #? 91644

4 EXISTING WELL CONSTRUCTION
Depth Drilled 960' Feet Depth Cased 960' Feet
EXISTING CASING SCHEDULE
Table with columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet).
Row 1: 4, 11.35, .25, 0', 960'

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: Air
From 305' feet to 500' feet Number of perfs per linear foot 12

Existing Perforations:
Type of perforation Vert Slot
Size of perforation 8" x 2"
From 560' feet to 960' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

5 WATER LEVEL
Static water level 407' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS
Material Used
From 960' feet to 0' feet Neat Cement 6 yards
Pumped Poured
From feet to feet Pumped Poured
Neat Cement Fluid Weight Thick lbs/gal
Bentonite Grout % bentonite

6 Additional Notes or Comments
Rig up over IW-9 - Clean Well to 960' - Lots of Dirt. Pull out & Put on perforator. Back in Well & perforate 305' -> 500' - Double Pass.
Perforator off & Run Trime in Well to 960' - mix cement & pump in lifts - 960' to 0'
6 yards of Neat cement Thick

Date Started 10-7-10
Date Completed 10-8-10

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Ward Weaver Rimmerk Drilling Contractor
Address 2305 Last Chance Rd. ELDON, NV. 89801 Contractor
Nevada contractor's license number issued by the State Contractor's Board 0030630
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676
Signed Ward Weaver By driller performing actual drilling on-site or contractor
Date 10-16-10