

21-1021

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 112238
Permit No. 444
Basin 65010

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. ~~65010~~

1 OWNER Yukon Nevada Gold Corp.
MAILING ADDRESS HC 31 BOX 78 ELKO, NV.
89801

ADDRESS AT WELL LOCATION Jerritt Canyon mine
East DASH
Subdivision Name: County:

2 LOCATION NE 1/4 NW 1/4 Sec 17 T 400 R 54 E
PERMIT/WAIVER No. MP-1321
Parcel No.

Latitude 41.2146, 83.301 UTM E 590142.26 NAD 27
Longitude 115.5520, 19.344 N 4579403.55 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a
replacement well was drilled? NO
If yes, what is replacement well NOI?

Is there an existing well log? yes
If yes, what is NDWR well log #? 95393

4 EXISTING WELL CONSTRUCTION
Depth Drilled 1090 Feet Depth Cased 1085 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1 7/8"	27	SEA-20 PK	0	1085

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:

Existing Perforations:
Type of perforation Horiz. slot
Size of perforation 1080
From 1085 feet to 435 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Type of perforator used:
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot

5 WATER LEVEL
Static water level 392' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS
Material Used

6 Additional Notes or Comments
Run Trimie Line into 1080' - Hook
to Head on Drill Rig & clean with
air.
mix & pump thick Neat cement
with grout tub.
pump T.D. to Surface in Lifts
as we pulled Trimie Line.
1 yard Cement

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From 1080'	feet to 0'	feet	Neat Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>

Neat Cement Fluid Weight Thick lbs/gal
Bentonite Grout % bentonite

Date Started 9-23-10
Date Completed 9-23-10

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true
to the best of my knowledge.

Name Ward Weaver Rimrock Drilling Contractor
Address 2305 Last Chance Rd. ELKO, NV. 89801 Contractor

Nevada contractor's license number issued by the State Contractor's Board 0030630

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676

Signed Ward Weaver By driller performing actual drilling on-site or contractor

Date 10-16-10