

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 112 239  
Permit No.  
Basin 044

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65008

1 OWNER Yukon Nevada Gold Corp ADDRESS AT WELL LOCATION Territt Canyon Mine  
MAILING ADDRESS HC 91 Box 78 ELKO, NV. 89801 East Dash  
Subdivision Name: County:

2 LOCATION SW 1/4 NE 1/4 Sec 17 T 40 N S R 54 E Latitude 412128.77207 UTM E 590636.39 NAD 27  
PERMIT/WAIVER No. Longitude 1155459.22588 N 4578852.65 NAD 83/WGS 84  
Issued by Water Resources Parcel No.

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? NO  
If yes, what is replacement well NOI?  
Is there an existing well log? yes  
If yes, what is NDWR well log #? 91681

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 460' Feet Depth Cased 460' Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4	11.35	.250	0	460

Existing Perforations:  
Type of perforation Vert slot  
Size of perforation .080  
From 460' feet to 260' feet  
From feet to feet  
From feet to feet  
From feet to feet  
From feet to feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used:  
From feet to feet Number of perms per linear foot  
From feet to feet Number of perms per linear foot  
From feet to feet Number of perms per linear foot  
From feet to feet Number of perms per linear foot  
From feet to feet Number of perms per linear foot  
From feet to feet Number of perms per linear foot

5 WATER LEVEL  
Static water level 60' feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature °F Quality

8 WELL PLUGGING MATERIALS  
Material Used  
From 460' feet to 0' feet Neat Cement  Pumped  Poured  
From feet to feet  Pumped  Poured

6 Additional Notes or Comments  
Ran Tremie Pipe to 460'  
Cleaned Well.  
Pumped Neat Cement  
in Lifts T.O. to surface  
with grout tub.  
2 yards cement

Neat Cement Fluid Weight THICK lbs/gal  
Bentonite Grout % bentonite  
Date Started 9-21-10  
Date Completed 9-22-10

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Ward Weaver - Rimrock Drilling Contractor  
Address 2345 Last Chance Rd, ELKO, NV. 89801 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 0030630  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676  
Signed Ward Weaver By driller performing actual drilling on-site or contractor  
Date 10-16-10