IW-8

# STATE OF NEVADA
# DIVISION OF WATER RESOURCES
# WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 112242
Permit No.
Basin 044

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65012

1 OWNER Yukon Nevada Gold Corp.
MAILING ADDRESS HC-31 Box 78 ELKO, NV. 89801

ADDRESS AT WELL LOCATION Jerritt Canyon Mine East DASH
Subdivision Name: County:

2 LOCATION NE¼ NW ¼ Sec 17 T 40 ⊙S R 54 ⊙
PERMIT/WAIVER No. Issued by Water Resources Parcel No.

Latitude 412141.74012
Longitude 1155516.01397
UTM E 596241.32 ☒ NAD 27
N 4579247.70 ☐ NAD 83/WGS 84

3 TYPE OF WELL Injection well X
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?

Is there an existing well log? yes
If yes, what is NDWR well log #? 86169

4 EXISTING WELL CONSTRUCTION
Depth Drilled 1000' Feet Depth Cased 1000' Feet

EXISTING CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 4 | 11.35 | .25 | 0' | 1000' |
| | | | | |
| | | | | |

Existing Perforations:
Type of perforation Vert. slot
Size of perforation 1/8 x 2"

| | | | |
|---|---|---|---|
| From 580' | feet to 1000' | feet | |
| From | feet to | feet | |
| From | feet to | feet | |
| From | feet to | feet | |
| From | feet to | feet | |

5 WATER LEVEL
Static water level 509' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

6 Additional Notes or Comments

Rig up over IW-8 - Run Trimie in well & clean well to 1000' pull Trimie & put perforator on.
Run in to 480' & perforate to 580' Double pass.
Pull Perforator out & Take off.
Run Trimie in well to 1000'
mix & pump Neat Cement in Lifts to Surface.
7 yards Cement.

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used: Air

| | | | |
|---|---|---|---|
| From 480' | feet to 580' | feet | Number of perfs per linear foot 12 |
| From | feet to | feet | Number of perfs per linear foot |
| From | feet to | feet | Number of perfs per linear foot |
| From | feet to | feet | Number of perfs per linear foot |
| From | feet to | feet | Number of perfs per linear foot |
| From | feet to | feet | Number of perfs per linear foot |

8 WELL PLUGGING MATERIALS

| | | | Material Used | |
|---|---|---|---|---|
| From 1000' | feet to 0' | feet | Neat Cement 7 yards | ☐ Pumped ☐ Poured |
| From | feet to | feet | | ☐ Pumped ☐ Poured |
| From | feet to | feet | | ☐ Pumped ☐ Poured |
| From | feet to | feet | | ☐ Pumped ☐ Poured |
| From | feet to | feet | | ☐ Pumped ☐ Poured |
| From | feet to | feet | | ☐ Pumped ☐ Poured |

Neat Cement Fluid Weight Thick lbs/gal
Bentonite Grout % bentonite
Date Started 10-6-10
Date Completed 10-7-10

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Ward Weaver Rimrock Drilling Contractor
Address 2305 Last Chance Rd. ELKO, NV. 89801 Contractor

Nevada contractor's license number issued by the State Contractor's Board 0030630
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676
Signed Ward Weaver By driller performing actual drilling on-site or contractor
Date 10-16-10

(Rev. 06-06)

USE ADDITIONAL SHEETS IF NECESSARY 41.361594°N 115.921115°W NAD 27 (T)

(NSPO 3-08) (O) 627A