

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 112249  
Permit No. 444  
Basin

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1 OWNER Yukon Nevada Gold Corp.  
MAILING ADDRESS HC 31 Box 78 ELKO NV 89801

ADDRESS AT WELL LOCATION Jonit Canyon Mine East DASH  
Subdivision Name: County:

2 LOCATION NE 1/4 NW 1/4 Sec 17 T 43 S R 59 E  
PERMIT/WAIVER No. Issued by Water Resources Parcel No.

Latitude 41.2143, 72.394 UTM E 590399.63 NAD 27  
Longitude 115.5509, 16.765 N 45.79310, 26 NAD 83/WGS 84

3 Exploration X TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? NO  
If yes, what is replacement well NOI?

Is there an existing well log? ? NO  
If yes, what is NDWR well log #? N/A

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 1080' Feet Depth Cased 20' Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

Existing Perforations:  
Type of perforation  
Size of perforation  
From feet to feet  
From feet to feet  
From feet to feet  
From feet to feet

If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforater used:  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot

5 WATER LEVEL  
Static water level 374' feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature °F Quality

8 WELL PLUGGING MATERIALS

Material Used			
From 1080' feet to 20' feet	Super Plug	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From 20' feet to 0' feet	Neat Cement	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From feet to feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From feet to feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From feet to feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From feet to feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured

6 Additional Notes or Comments  
The Mine has this Hole as IMW-10 Pilot. So it Be called. It was Drilled as an exploration Hole & when water was Hit they put 20' of 2" casing hanging in surface casing. off set & drilled IMW-10 Injection well.  
We pulled the 20' x 2" pipe out  
Re-entered with Drill pipe & Tri. Cone to 1080' & cleaned Hole.  
Trip & Abandon TD. up -  
45 Bags of Super Plug mixed & pumped in with 2" as we tripped.  
Cement Top 20'

Neat Cement Fluid Weight lbs/gal  
Bentonite Grout % bentonite  
Date Started 9-22-10  
Date Completed 9-22-10

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Ward Weaver - Rimrock Drilling  
Address 2305 Last Chance Rd. ELKO, NV. 89801

Nevada contractor's license number issued by the State Contractor's Board 0030630  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676  
Signed Ward Weaver  
Date 10-16-10

USE ADDITIONAL SHEETS IF NECESSARY  
41.362146°N  
115.919213°W  
NAD 27