

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 112245  
Permit No. 60231  
Basin Q28

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64934

1 OWNER HYCROFT RESOURCES ADDRESS AT WELL LOCATION SULPHER  
MAILING ADDRESS PO BOX 3030 WINNEMUCCA NV, 89445

2 LOCATION NE 1/4 NE 1/4 Sec 31 T 35N N/S R 29 E Latitude 40° 52.188 N UTM E  NAD 27  
PERMIT/WAIVER No. 60231 Longitude 118° 46.285 W N  NAD 83/WGS 84  
Issued by Water Resources Parcel No.

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? YES  
If yes, what is replacement well NOI? 64933  
Is there an existing well log? YES  
If yes, what is NDWR well log #? 28898

4 EXISTING WELL CONSTRUCTION

Depth Drilled	440' Feet	Depth Cased	426' Feet
---------------	-----------	-------------	-----------

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
14"		.250"	+1'	204'
12 3/4"		.250"	204'	426'

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:

Existing Perforations:

Type of perforation	Size of perforation	MILL SLOT & SCREEN
From	142'	feet to 202' feet
From	284'	feet to 424' feet
From		feet to feet
From		feet to feet
From		feet to feet

Type of perforator used: HOLT AIR PERFORATOR

From	feet to	feet	Number of perfs per linear foot	Rows
From	50'	feet to 142'	feet	6 Rows
From	204'	feet to 284'	feet	6 Rows
From		feet to feet		
From		feet to feet		
From		feet to feet		
From		feet to feet		

5 WATER LEVEL  
Static water level 90' feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature ° F Quality

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From	0'	feet to 20'	NEAT CEMENT	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From	20'	feet to 424'	BENTONITE GROUT	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From		feet to feet		<input type="checkbox"/>	<input type="checkbox"/>
From		feet to feet		<input type="checkbox"/>	<input type="checkbox"/>
From		feet to feet		<input type="checkbox"/>	<input type="checkbox"/>
From		feet to feet		<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments  
NAD-27 G.P.S  
40.869899°N  
118.770418°W  
Plugging of Well Log 28898  
Replacement Well under Log 112028,

Neat Cement Fluid Weight 15 LBS lbs/gal  
Bentonite Grout 20% % bentonite  
Date Started 9/10/2010  
Date Completed 9/11/2010

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Hydro Resources - West Contractor  
Address 4975 W. Winnemucca Blvd. Contractor  
Winnemucca, NV 89445  
Nevada contractor's license number 56797  
issued by the State Contractor's Board  
Nevada driller's license number issued by the # 1713  
Division of Water Resources, the on-site driller  
Signed [Signature]  
By driller performing actual drilling on site or contractor  
Date 9-21-10