STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 112607
Permit No.
Basin 069

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66721

1. OWNER: Bernard S. Cannon Family Trust
MAILING ADDRESS: 7480 Western Horizon Dr, Winnemucca, Nv 89445

ADDRESS AT WELL LOCATION: 4305 Winchester Dr, Winnemucca, Nv 89445
Subdivision Name: 0 County: Humboldt

2. LOCATION SE ¼ NW ¼ Sec 2 T 39N N/S R 38E E
PERMIT/WAIVER No. 0 (issued by Water Resources) Parcel No. 006-101-04

Latitude 41 17.254n Longitude 117 40.265w
UTM E N NAD 27 [X]

3. WORKED PERFORMED: [X] New Well, Replace, Recondition, Deepen, Other

4. PROPOSED USE: [X] Domestic, Irrigation, Test, Municipal/Industrial, Monitor, Stock

5. WELL TYPE: Cable [X] Rotary, RVC, Air, Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy loam top soil		0	5	5
Med gravel clay & sand		5	10	5
Sand, small gravel & cobbles		10	80	70
Sand, med gravel		80	160	80
		160		
				160.00

Date started: 12/22/2010
Date completed: 12/25/2010

RECEIVED 2011 JAN -7 AM 10:56 STATE ENGINEER'S OFFICE

9. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160

HOLE DIAMETER (BIT SIZE)

		From		To	
10 7/8	Inches	0	Feet	160	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	STEEL	.188	0	20
6.900	PVC	sdr21=.450 in	20	160

Perforations:
Type of perforation: 6 inch pvc mill horizontal slot screen
Size of perforation: 1/32

From	120	feet to	160	feet
From		feet to		feet
From		feet to		feet
From		feet to		feet
From		feet to		feet

Annular Seal: [X] Yes

Neat Cement	to		Pumped	Poured
Cement Grout	4 to	80	Pumped	[X]
Concrete Grout	to		Pumped	Poured
≥30% Bentonite Grout	to		Pumped	Poured

Gravel Pack: [X] Yes No 100 to 160 Pumped [X]
Type: 3/8 minus
Bentonite Chips: [X] Yes No 80 to 100 Pumped [X]
Type: 3/8 baroid

7. Water Level
Static water level: 86 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: COLD °F
Quality:

8. WELL TEST DATA
TEST METHOD: Bailer Pump Air Lift x

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AIR			4

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor): High Desert Drilling LLC
Address (Contractor): 4225 E Mary Way
Winnemucca Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board: 62237
Nevada driller's license number issued by the Division of Water Resources, for on-site driller: 2140
Signed (By driller performing actual drilling on site or contractor): # 2364
Date: January 3, 2011

USE ADDITIONAL SHEETS IF NECESSARY

41.287862°N
117.670259°W
NAD 27 (7A)