

Decontaminating Well D-2nd

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 113045
Permit No. 087
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

1 OWNER Nevada Air National Guard
MAILING ADDRESS 458/4702 3500 Fletcher AV
Joint Base Andrews, MD 20762

ADDRESS AT WELL LOCATION 152nd Air Filt Wing
Nevada Air National Guard, Reno NV
Subdivision Name County

NOTICE OF INTENT NO. 66325

2 LOCATION 58th 4th NE 1/4 Sec 19 T 19 S R 20 E
PERMIT/WAIVER No. 015-240-24
Latitude Longitude
UTME N
 NAD 27
 NAD 83/WGS 84

3 Extraction TYPE OF WELL Air Sparger
 Domestic Soil Vapor Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?
Is there an existing well log?
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 25 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4		schd 40	0	25

Existing Perforations:
Type of perforation
Size of perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
To limit waste to be disposed

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used:
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot

5 WATER LEVEL
Static water level 8 ft feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS

Material Used
From 0 feet to 25 feet Cement Pumped Poured
From feet to feet Pumped Poured

6 Additional Notes or Comments
Abandonment method
1.) Backhamer cut well logs
2.) Air lift to set logs
3.) Knock out bottom of well
4.) Tremie grout
5.) Pressure grout @ 25 psi for 10min
6.) Pull casing
7.) Top off wells with cement
8.) concrete surface patch

Neat Cement Fluid Weight lbs/gal
Bentonite Grout % bentonite
Date Started September 20th, 2010
Date Completed October 25th, 2010

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge
Name RSI Drilling Contractor
Address 220 W East Street Woodland, CA 95776 Contractor
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2422-M
Signed [Signature]
Date 9-25-10
By driller performing actual drilling on site or contractor

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY