STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 113435
Permit No. 46722
Basin 029

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66850

1. OWNER Egger Enterprises, LLC
MAILING ADDRESS High Desert Farm Hwy 140
ADDRESS AT WELL LOCATION Winnemucca, NV 89445

2. LOCATION NW¼ NE ¼ Sec 28 T 44N N/S R 31 E
PERMIT/WAIVER No. 46722/13314 *Issued by Water Resources* Parcel No.
Latitude 41deg 39.897min N
Longitude 118deg 30.509 W
UTM E N
☐ NAD 27 ☑ NAD 83/WGS 84
Subdivision Name: County: Humboldt

3. WORKED PERFORMED
☐ New Well ☑ Replace ☐ Recondition ☐ Deepen ☐ Other...

4. PROPOSED USE
☐ Domestic ☑ Irrigation ☐ Test ☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☑ RVC ☐ Air ☐ Other...

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Topsoil		0	5	5
Fine Granite Sand		5	50	45
Course Granite Sand & Gravel		50	70	20
Small Gravel		70	80	10
Course Granite Sand & Gravel		80	100	20
Course Sand, Gravel & Clay		100	110	10
Small Gravel	X	110	190	80
Small Gravel & Clay	X	190	240	50
Soft Brown Clay		240	290	50
Large Gravel & Cobbles In Clay		290	400	110
Soft Brown Clay With DG		400	540	140

RECEIVED 2011 MAR 28 AM 11:53 STATE ENGINEER

Date started 2/14/2011 , 20
Date completed 2/17/2011 , 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☑ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Pump	600	185	12
		PL 350ft	

8. WELL CONSTRUCTION
Depth Drilled 540 Feet Depth Cased 520 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
42	Inches	0	Feet	50	Feet
28	Inches	50	Feet	540	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
36		.250	0	50
16		.250	+1	520

Perforations:
Type of perforation Mill Slot
Size of perforation .250" x 3"
From 120 feet to 520 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 50ft
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 0 feet to 540 feet

9. WATER LEVEL
Static water level 165 feet below land surface
Artesian flow NA G.P.M P.S.I
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name AMS Enterprises (Contractor)
Address 399 Denio Hwy 140, Winnemucca, NV 8945 (Contractor)
Nevada contractor's license number issued by the *State Contractor's Board* 58683
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2140
Signed (By driller performing actual drilling onsite or contractor)
Date 3/23/11

(Rev. 06/10) **USE ADDITIONAL SHEETS IF NECESSARY**

41.665052°N
118.507485°W
NAD 27 (TA)