STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 113798
Permit No.
Basin 090

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 57610

1. OWNER Chevron Environmental Management
MAILING ADDRESS 6001 Bollinger Canyon Road
San Ramon, CA 94583

ADDRESS AT WELL LOCATION 947 Tahoe Blvd. MW-11
Incline Village, NV
Subdivision Name: County: Washoe

2. LOCATION NW ¼ SE ¼ Sec 15 T 16N N/S R 18 E
PERMIT/WAIVER No. 132-231-10
Issued by Water Resources Parcel No.

Latitude 39° 14' 943.8" N
Longitude 119° 56' 755.2" W
UTM E ~~4985.80~~
N ~~5001.25~~
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Poorly graded silty sand, fine to		0	15	15
med. grain, brown, rounded, dry				
Poorly graded silty sand, fine to		15	20	5
med. grain, brown, rounded, dry				
Poorly graded silty sand,		20	25	5
rounded, brown, moist, fine to				
medium grain				
Poorly graded sand, trace silt		25	35	10
rounded, brown, moist, coarse				
Poorly graded sandy silt, brown,		35	40	5
wet				

Date started: 30-May, 20 06
Date completed: 30-May, 20 06

9. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
2	Inches	0	Feet	40	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sch 40	0	~~25~~ 40

Perforations:
Type of perforation slot
Size of perforation .020
From 25 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 0 to 18 ☒ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 20 to 40 ☐ Pumped ☒ Poured
Type: #3 Sand
Bentonite Chips: ☒ Yes ☐ No 18 to 20 ☐ Pumped ☒ Poured
Type: Bentonite Chips

7. Water Level
Static water level: 28 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cascade Drilling, L.P. (Contractor)
Address 3632 Omec Circle (Contractor)
Rancho Cordova, CA 95742
Nevada contractor's license number issued by the *State Contractor's Board* C23-51207 / C23-0073966
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-1977
Signed (By driller performing actual drilling on site or contractor)
Date 10-Mar-10

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

39.249064° N NAD27
119.945919° W