

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 11385  
Permit No. \_\_\_\_\_  
Basin \_\_\_\_\_

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 35071

1. OWNER 4-G Properties, LTD / TRIDENT TRUST DOWNER ADDRESS AT WELL LOCATION 4235 East Charleston Boulevard  
MAILING ADDRESS 30240 Ranch Viejo Road Las Vegas, Nevada 89104  
San Juan Capistrano, California 92675 MW-25

2. LOCATION NW 1/4 NW 1/4 Sec 5 T 21S N/S R 62 E Latitude 36 09 30.68 UTM E  NAD 27  
PERMIT/WAIVER No. 161-05-110-003 Longitude 115 04 55.14 N  NAD 83/WGS 84  
Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name: \_\_\_\_\_ County: Clark

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other...  
4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other... HAS

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>clay</u>		<u>0</u>	<u>10</u>	<u>16</u>
<u>silty clayey sand</u>		<u>10</u>	<u>12</u>	<u>2</u>
<u>clay silt &amp; sand</u>	<input checked="" type="checkbox"/>	<u>12</u>	<u>34</u>	<u>22</u>
<u>sand with clay &amp; silt</u>	<input checked="" type="checkbox"/>	<u>34</u>	<u>44</u>	<u>10</u>
<u>clay</u>	<input checked="" type="checkbox"/>	<u>44</u>	<u>47</u>	<u>3</u>

8. WELL CONSTRUCTION  
Depth Drilled 45.5 Feet Depth Cased 45 Feet  
HOLE DIAMETER (BIT SIZE)  
From To  
18 Inches 0 Feet 33 Feet  
8 Inches 33 Feet 45.5 Feet  
CASING SCHEDULE  
Size O.D. (Inches) Weight/Ft. (Pounds) Wall Thickness (Inches) From (Feet) To (Feet)  
4.5 2.05 0.237 0   
1.3 0.32 0.133 0   
10.75 7.91 0.365 0 33  
Perforations:  
Type of perforation \_\_\_\_\_ Factory Cut  
Size of perforation 0.020"  
From 35 feet to 45 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Surface Seal:  Yes  No Seal Type:  
Depth of Seal 0-30  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
Gravel Packed:  Yes  No  
From 34 feet to 45.5 feet  
9. WATER LEVEL  
Static water level 15 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

DCNR/DWR  
RECEIVED

APR 25 2011

LAS VEGAS OFFICE

Date started 3-Jan , 20 11  
Date completed 14-Jan , 20 11

7. WELL TEST DATA

TEST METHOD:  Bailor  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Yellow Jacket Drilling Services  
Contractor  
Address P.O. Box 801, Gilbert, AZ 85299  
Contractor  
Nevada contractor's license number issued by the State Contractor's Board 0058304A  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2341  
Signed [Signature]  
By driller performing actual drilling on site or contractor  
Date 2-13-11

(Rev. 06/10)

USE ADDITIONAL SHEETS IF NECESSARY