STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 113861
Permit No.
Basin 053

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66486

1 OWNER FASKIN OIL & RANCH LTD
MAILING ADDRESS 303 WALL AVE #1800
MIDLAND, TX 79701

ADDRESS AT WELL LOCATION PAPOOSE CANYON
PAPOOSE CANYON #14, FEDERAL #1
Subdivision Name: BLM LAND County: EUREKA

2 LOCATION NE ¼ SE ¼ Sec 15 T 29N N/S R 52 E
PERMIT/WAIVER No. OG-260 (Issued by Water Resources) Parcel No.

Latitude
Longitude
UTM E 11T 0577400 [X] NAD 27
N 4471700 [ ] NAD 83/WGS 84

3 TYPE OF WELL (oil/gas exploration)
[ ] Domestic [ ] Irrigation [ ] Test
[X] Municipal/Industrial [ ] Monitor [ ] Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?

Is there an existing well log? YES
If yes, what is NDWR well log #? 110007

4 EXISTING WELL CONSTRUCTION
Depth Drilled 550 Feet Depth Cased 550 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	17	.188	+2	550

Existing Perforations:
Type of perforation MACHINE MILLED
Size of perforation 3/16" X 3", 8 ROWS

From	282	feet to	345	feet
From	366	feet to	386	feet
From	407	feet to	427	feet
From	448	feet to	468	feet
From	489	feet to	529	feet

5 WATER LEVEL
Static water level 158 feet below land surface
Artesian flow NO G.P.M. P.S.I
Water temperature 63 °F Quality GOOD

6 Additional Notes or Comments

DUG DOWN 3' DEEP AROUND THE CASING AND CUT THE CASING OFF AT CEMENT LEVEL INSIDE OF CASING

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [X] yes [ ] no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? [ ] yes [X] no
Was the casing pulled? [ ] yes [X] no
Was the casing over drilled? [ ] yes [X] no
If casing was left in place, please show where additional perforations were made:

Additional Perforations:
Type of perforater used: HOLTZ PERF TOOL

From	100	feet to	282	feet	Number of perfs per linear foot	5
From	345	feet to	366	feet	Number of perfs per linear foot	5
From	386	feet to	407	feet	Number of perfs per linear foot	5
From	427	feet to	448	feet	Number of perfs per linear foot	5
From	468	feet to	489	feet	Number of perfs per linear foot	5
From	529	feet to	550	feet	Number of perfs per linear foot	5

8 WELL PLUGGING MATERIALS

					Material Used		
From	3	feet to	550	feet	NEAT CEMENT	[X] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured

Neat Cement Fluid Weight 13.5 lbs/gal
Bentonite Grout % bentonite
Date Started 2-May-11
Date Completed 4-May-11

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING INC (Contractor)
Address P. O. BOX 850 (Contractor)
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1653
Signed (By driller performing actual drilling on site or contractor)
Date 6-May-11

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

RECEIVED 2011 MAY 17 AM 11:59 STATE ENGINEER'S OFFICE

40.394205°N
116.088013°W NAD27