STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 113917
Permit No.
Basin 054

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62041

1. OWNER Marvin Fairbanks
MAILING ADDRESS 2346 President Blvd
SW Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION Pioneer Pass #2 Lot 9
Chaps Cir
Subdivision Name: County: Eureka

2. LOCATION ~~SE~~ ¼ NW ¼ Sec 19 T 31N N/S R 50 E
PERMIT/WAIVER No 003-471-06
Issued by Water Resources Parcel No.

Latitude 40.32.792N
Longitude 116.23.336W
UTM E N NAD83
☐ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Loam		0	15	15
Aluvel Fill		15	125	110
Conglomerate		125	225	100
Broken Rock		225	245	20
Sand and Gravel	X	245	265	20

Date started: 11-Apr , 20 08
Date completed: 15-Apr , 20 08

7. Water Level
Static water level 210 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cold °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
APPROX	40		3.5

9. WELL CONSTRUCTION
Depth Drilled 265 Feet Depth Cased 265 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	265	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.92	188	+1	265

Perforations
Type of perforation Mill Slot
Size of perforation 3/16 x 3"
From 245 feet to 265 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 18 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 31 to 265 ☐ Pumped ☒ Poured
Type: 3/8 PEA GRAVE;
Bentonite Chips: ☒ Yes ☐ No 18 to 51 ☐ Pumped ☒ Poured
Type: 3/4 Kiwk Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name SHAREL C. FERTIG SR. dba FERTIG DRILLING COMPANY
Contractor
Address P.O. BOX 525
Contractor
ELKO, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 031904
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1584
Signed
By driller performing actual drilling on site of contractor
Date 5-15-08

(Rev. 05-03)

USE ADDITIONAL SHEETS IF NECESSARY

40.546617°N NAD27
116.388018°W D.D.

MMH