STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 113963
Permit No.
Basin 137A

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66734

1. OWNER: Prock,J&T trs, and Smith, H&N trs
MAILING ADDRESS: 7200 Circle Pkwy
Sacramento, Ca 95823

ADDRESS AT WELL LOCATION: MW-4
NV2010109
Subdivision Name: County: Nye

2. LOCATION NE ¼ NW ¼ Sec 24 T 8 N N/S R 39E E
Latitude UTM E 11 452334
PERMIT/WAIVER No. 001-521-06 Longitude N 4266514 X NAD 27
Issued by Water Resources Parcel No.

3. WORKED PERFORMED: X New Well, Replace, Recondition, Deepen, Other
4. PROPOSED USE: Domestic, Irrigation, Test, Municipal/Industrial, X Monitor, Stock
5. WELL TYPE: Cable, X Rotary, RVC, Air, Other see notes

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil, Sand & Gravel		0	10	10
Cobbles,Gravel,Sand & Clay	x	10	32	22
		32		
				32.00

Date started: 5/26/2011
Date completed: 5/28/2011

9. WELL CONSTRUCTION
Depth Drilled 32 Feet Depth Cased 32

HOLE DIAMETER (BIT SIZE)

		From		To	
8 1/2	Inches	0	Feet	10	Feet
6.5	Inches	10	Feet	32	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4 1/2		sch 40	3.5 agl	32

Perforations:
Type of perforation: horizontal mill cut
Size of perforation: 0.01
From 7 feet to 27 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: Yes
Neat Cement 0 to 2 X Poured
Cement Grout to Poured
≥30% Bentonite Grout to Poured

Gravel Pack: X Yes No 6 to 32 Pumped X Poured
Type: SILICA SAND
Bentonite Chips: Yes 2 to 6 X Poured
Type: 3/8 casing seal

7. Water Level
Static water level: 12.33 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cold °F
Quality: good

8. WELL TEST DATA
TEST METHOD: Bailer, X Pump, Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Well produces about 5 gpm	0.5	

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Contractor: High Desert Drilling LLC
Address Contractor: 4225 E Mary Way
Winnemucca Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board: 62237
Nevada driller's license number issued by the Division of Water Resources the on-site driller: 2364
Signed By driller performing actual drilling on site or contractor: Roger N. Johnson
Date: May 29, 2011

(Rev. 05-08) USE ADDITIONAL SHEETS IF NECESSARY
Drilled with bentonite slurry. Then developed with pump.

38.545843°N NAD 27 TA
117.546052°W