STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 113965
Permit No.
Basin 137A

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66734

1. OWNER: Prock,J&T trs, and Smith, H&N trs
MAILING ADDRESS: 7200 Circle Pkwy
Sacramento, Ca 95823

ADDRESS AT WELL LOCATION: MW-2
NV2010109
Subdivision Name:
County: Nye

2. LOCATION NE ¼ NW ¼ Sec 24 T 8 N N/S R 39E E
PERMIT/WAIVER No. 001-521-06
Issued by Water Resources
Parcel No.

Latitude
Longitude
UTM E 11 452273
N 4266425
[X] NAD 27 [ ] NAD 83

3. WORKED PERFORMED
[X] New Well Replace Recondition
Deepen Other

4. PROPOSED USE
Domestic Irrigation Test
Municipal/Industrial [X] Monitor Stock

5. WELL TYPE
Cable [X] Rotary RVC
Air Other see notes

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil, Sand & Gravel		0	7	7
Cobbles,Gravel,Sand & Clay	x	7	32	25
		32		
				32.00

Date started: 5/26/2011
Date completed: 5/28/2011

9. WELL CONSTRUCTION
Depth Drilled 32 Feet Depth Cased 32

HOLE DIAMETER (BIT SIZE)

		From		To	
8 1/2	Inches	0	Feet	7	Feet
6.5	Inches	7	Feet	32	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4 1/2		sch 40	3.1 agl	32

Perforations:
Type of perforation: horizontal mill cut
Size of perforation: 0.02
From 7 feet to 27 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes
Neat Cement 0 to 2 [X] Poured
Cement Grout to Poured
≥30% Bentonite Grout to Poured

Gravel Pack: [X] Yes No 6 to 32 [X] Poured
Type: SILICA SAND
Bentonite Chips: [X] Yes 2 to 6 [X] Poured
Type: 3/8 casing seal

7. Water Level
Static water level: 12.13 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cold °F
Quality: good

8. WELL TEST DATA
TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Well produces about 6 gpm		

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name of Contractor: High Desert Drilling LLC
Address of Contractor: 4225 E Mary Way
Winnemucca Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board: 62237
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 2364
Signed (By driller performing actual drilling on site or contractor): Roger N. Johnson
Date: May 29, 2011

(Rev. 06-08) USE ADDITIONAL SHEETS IF NECESSARY
Drilled with bentonite slurry. Then developed with pump

38.545038°N
117.546746°W NAD 27 (TA)