STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 114227
Permit No.
Basin 101

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67522

1. OWNER CHARLES AND HAZEL GOMES
MAILING ADDRESS 5643 SOLIAS RD
FALLON, NV 89406

ADDRESS AT WELL LOCATION 5643 SOLIAS RD
FALLON, NV 89406
Subdivision Name: County: Churchill

2. LOCATION NW ¼ SW ¼ Sec 22 T 18N N/S R 28 E
PERMIT/WAIVER No. SW (TA) 006-436-01
Issued by Water Resources Parcel No.

Latitude 39.40810*N
Longitude 118.83636*W
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well ☒ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC ☐ Air ☒ Other MUD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
OVER BURDEN		0	3	3
COURSE DG SANDS		3	25	22
GRAY SANDS		25	30	5
BLACK SILTY SANDS		30	48	18
GREEAN SANDS AND CLAY	XX	48	70	22
GRAY COURSE SANDS AND CLAY	X	70	80	10

RECEIVED 2011 AUG 11 PM 1:11 STATE ENGINEERS OFFICE

Date started: 02-Aug, 20 11
Date completed: 11 11, 20 11

9. WELL CONSTRUCTION
Depth Drilled 80' Feet Depth Cased 80 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12 1/4	Inches	0	Feet	80	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.03	.188	1 1/2	20
6 5/8	4.26	.216	20	80
SDR 21				

Perforations:
Type of perforation FACTORY SLOT
Size of perforation .032
From 60 feet to 80 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 0 to 50 ☒ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 50 to 80 ☐ Pumped ☒ Poured
Type: PEAT GRAVEL
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 10 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: COLD °F
Quality: GOOD

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25	10	3 HRS

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name CAPITAL CITY WELL DRILLING AND PUMP SERVICE INC. (Contractor)
Address 20 KIT KAT DRIVE (Contractor)
CARSON CITY, NV 89706
Nevada contractor's license number issued by the *State Contractor's Board* 0055548
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1905
Signed (By driller performing actual drilling on site or contractor)
Date 08/05/2011

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

39.408187°N
-118.835374°W
NAD 27 (TA)