STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 114341
Permit No. 80116
Basin 070

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65459

1. OWNER Keith Kubicheck
MAILING ADDRESS 4062 W. Winnemucca Blvd.

ADDRESS AT WELL LOCATION Jungo Road
Winnemuca, NV 89445
Subdivision Name: County: humboldt

2. LOCATION NW¼SW¼ Sec29T36N/ R37E
PERMIT/WAIVER NO. 80116 (Issued by Water Resources) N/A (Parcel, No.)

Latitude N40°57961 UTM E ☐ NAD 27
Longitude W117°50894 N ☒ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand/clay		0	10	10
Sand/course gravel		10	70	60
boulders/clay		70	90	20
clay w/rock		90	100	10
cobles & gravel	X	100	165	65
clay		165	185	20
gravel/sand	X	185	225	40
clay		225	230	5
gravel/cobles	X	230	240	10
clay		240	260	20
gravel/sand	X	260	300	40

RECEIVED 2011 SEP 15 AM 11:28 STATE ENGINEER

Date started: Aug 29, 20 11
Date completed: Sept 2, 20 11

9. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12 5/8 Inches	0 Feet	300 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	15	188	+1	300

Perforations:
Type of perforation Factory Cut Slots
Size of perforation 3/32x4
From 140 feet to 180 feet
From 200 feet to 220 feet
From 260 feet to 300 feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 57 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 57 to 300 ☐ Pumped ☒ Poured
Type:
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 90 feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I
Water Temperature: Cool °F
Quality: Fair

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50-125		4

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Fred Anderson Drilling, Inc. (CONTRACTOR)
Address 10760 S. Grass Valley Road (CONTRACTOR)
Winnemucca, NV 89445
Nevada contractor's license number issued by the State Contractor's Board 021467
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2083
Signed Fred Anderson Drilling Inc
By driller performing actual drilling on site or contractor
Date September 13, 2011

(Rev 05-06) USE ADDITIONAL SHEETS IF NECESSARY

Forms Provided by Forms-On-A-Disk · (214) 340-9429 · FormsOnADisk.com

40.966114°N ; -117.847267°W
NAD 27 TA