STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 114796
Permit No.
Basin 084

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66462

1. OWNER The Boeing Company
MAILING ADDRESS 5800 Woolsey Cnyn. Rd.
Canoga Park, CA 91304

ADDRESS AT WELL LOCATION 800 C Axe Handle Cnyn. Rd.
Reno, NV 89510
Subdivision Name: County: Washoe

2. LOCATION NW¼SE¼ Sec29T22N/ R21E
PERMIT/WAIVER NO. D-000543 (Issued by Water Resources) 076-150-01 (Parcel. No.)

Latitude 39.745575 UTM E ☐ NAD 27
Longitude 119.645788 N ☒ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Weatherd Granite		0	14	14
Clay Zone		14	16	2
Weatherd Granite		16	69	53
Weatherd Volcanic, W/ Granite		69	126	57
Small Fracture,Weatherd Vol.		126	157	31
Fracture		157	158	1
Gray Volcanics		158	221	63
Brown Weatherd Volcanics		221	320	99
Gray Hard Volcanic		320	360	40
Fractured	X	360	365	5
Gray Hard Volcanic		365	392	27
Fractured		392	394	2
Gray Hard Volcanic		394	415	21

WELL
B26A

Date started: 8-15, 20 11
Date completed: 8-19, 20 11

7. Water Level
Static water level: 314.5 feet below land surface
Artesian Flow: G.P.M. P.S.I
Water Temperature: cool °F
Quality: not tested

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
4.5		3

39.745666 NAD27
119.644769

9. WELL CONSTRUCTION
Depth Drilled 415 Feet Depth Cased 415 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 5/8 Inches	0 Feet	415 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	8.66	.188	+2	415

Perforations:
Type of perforation Factory
Size of perforation 3/32 x 3"
From 355 feet to 415 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 340 to 0 ☒ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 415 to 345 ☐ Pumped ☐ Poured
Type: 1/4 x 1/8
Bentonite Chips: ☒ Yes ☐ No 345 to 340 ☐ Pumped ☒ Poured
Type: 3/8 coated

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Bruce MacKay Pump & Well Service, Inc. (CONTRACTOR)
Address 1600 Mt. Rose Hwy (CONTRACTOR)
Reno, NV 89511
Nevada contractor's license number issued by the State Contractor's Board 23095 23096
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed R. Bruce MacKay
By driller performing actual drilling on site or contractor
Date 8-22-11

RECEIVED 2011 SEP 1 AM 11:31 STATE ENGINEER'S OFFICE

(Rev 05-06) USE ADDITIONAL SHEETS IF NECESSARY

Forms Provided by Forms-On-A-Disk · (214) 340-9429 · FormsOnADisk.com