

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 115062  
Permit No. 80457  
Basin 055

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66302

1. OWNER Slagowski Ranches ADDRESS AT WELL LOCATION Pine Valley  
MAILING ADDRESS HC 65 Box 36 Subdivision Name: \_\_\_\_\_ County: Eureka  
Carlin, NV 89822

2. LOCATION SE 1/4 SE 1/4 Sec 22 T 28N N/S R 52 E Latitude W116°05.361 UTM E  NAD 27  
PERMIT/WAIVER No. 70195-80457 Longitude N40°17.358 N  NAD 83/WGS 84  
Issued by Water Resources Parcel No. \_\_\_\_\_

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
top soil		0	2	2
silt stone		2	20	18
silt stone & gravel		20	60	40
brown clay		60	120	60
gravel	x	120	125	5
silt stone		125	145	20
gravel	x	145	155	10
brown clay		155	170	15
gravel	x	170	185	15
brown clay		185	200	15
gravel	x	200	215	15
silt stone		215	240	25
gravel		240	260	20
brown clay		260	270	10

9. WELL CONSTRUCTION  
Depth Drilled 270 Feet Depth Cased 265 Feet  
HOLE DIAMETER (BIT SIZE)  
From 0 To 270  
Inches Feet Feet Feet  
Inches Feet Feet Feet  
Inches Feet Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
14		.250	+1 1/2	265

Perforations:  
Type of perforation mill slot  
Size of perforation 33/16 x  
From 115 feet to 265 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No  
 Neat Cement 0 to 100  Pumped  Poured  
 Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 ≥30% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No 100 to 265  Pumped  Poured  
Type: pea gravel  
Bentonite Chips:  Yes  No \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
Type: \_\_\_\_\_

Date started: 25-Oct \_\_\_\_\_, \_\_\_\_\_ 20\_\_\_\_ 11\_\_\_\_  
Date completed: 28-Oct \_\_\_\_\_, \_\_\_\_\_ 20\_\_\_\_ 11\_\_\_\_

7. Water Level  
Static water level: 1 feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: cold °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:  Bailor  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
800+		7

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name \_\_\_\_\_ Alternative Drilling Contractor  
Address P.O. Box 281166 Contractor  
Lamoille, NV 89828  
Nevada contractor's license number \_\_\_\_\_  
issued by the State Contractor's Board 73955  
Nevada driller's license number issued by the \_\_\_\_\_  
Division of Water Resources, the on-site driller 1689  
Signed \_\_\_\_\_  
Date 11-21-2011

(Rev. 12-08) USE ADDITIONAL SHEETS IF NECESSARY  
577406 E  
4460055 N  
NAD27  
Dec/Dec  
40.289303  
116.089354  
NAD27