

RNW-0005

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 115164
Permit No. 52236
Basin 49

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60553
62374

1 OWNER NEWMONT Ltd Corp
MAILING ADDRESS 11655 MOUNTAIN LODGE HWY
EIKO NEV 89801
ADDRESS AT WELL LOCATION RAIN ROAD, 5 MILES
"RAIN MINE"
Subdivision Name: County: EUREKA

2 LOCATION SE 1/4 SW 1/4 Sec 13 T 32 N R 52 E
PERMIT/WAIVER No. R-681 52236
Latitude 527888 NAD 27
Longitude 4500617 NAD 83/WGS 84

3 TYPE OF WELL
Municipal/Industrial
Irrigation
Test
Monitor
Stock
Is this well being plugged because a replacement well was drilled? YES
If yes, what is replacement well NOI? 60553
Is there an existing well log? YES
If yes, what is NDWR well log #? 28691

4 EXISTING WELL CONSTRUCTION
Table with columns: Size O.D. (Inches), Weight/Vt. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet)
Rows: 16, 42.05, .250, +1, 50; 8 5/8, 22.36, .250, +1, 850

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? no
If well was not cleaned out to total depth, please explain why: stuck in hole, sandbed in
Was the well contaminated? no
Was the casing pulled? no
Was the casing over drilled? no

Existing Perforations:
Type of perforation: 1/8" x 3" MILLER SLOT
Size of perforation: 400 feet to 840 feet

Additional Perforations:
Type of perforator used: STAR
Table with columns: From, feet to, Number of perfs per linear foot
Rows: 320 feet to 400 feet, 20 perfs; 20 feet to 0 feet, 20 perfs

5 WATER LEVEL
Static water level: 371 feet below land surface
Artesian flow: N/A
Water temperature: N/A

8 WELL PLUGGING MATERIALS
Material Used: NEAT CEMENT
Table with columns: From, feet to, Pumped, Poured
Rows: 427 feet to 0 feet, Pumped, Poured

6 Additional Notes or Comments
PUMP SANDED IN, PULLED 427'
COLUMN PIPE OUT OF HOLE.
PERPED CASING FROM 320' 400'
AND 0-20' PUMPED NEAT
CEMENT FROM 427' TO SURFACE
360 94lb CEMENT BAGS WERE
USED TO ABANDON HOLE
3400 GALS OF NEAT CEMENT.

Neat Cement Fluid Weight 15.2 lbs/gal
Bentonite Grout % bentonite
Date Started 9-15-11
Date Completed 9-22-11

Vertical stamp: STATE ENGINEER
Vertical stamp: 2011 OCT 3 01:03
Vertical stamp: 100 LBS

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name: BOB LONGYEAR
Address: P.O. BOX 2748 EIKO NEVADA 89803
Nevada contractor's license number: 0073086
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 1777
Signed: Dennis L. White
Date: 9-23-11

40.654643° N
116.078704° W
USE ADDITIONAL SHEETS IF NECESSARY