

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
 Log No. 115170
 Permit No. 80331E
 Basin 049

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67098 ✓

1. OWNER NV ENERGY ADDRESS AT WELL LOCATION NV ENERGY, 800 SILVER STREET, ELKO, NV.
 MAILING ADDRESS PO BOX 10100, RENO, NV., 89520

2. LOCATION SE 1/4 NE 1/4 Sec 15 T 34N N/S R 55 E Latitude N 40.83383° UTM E NAD 27
 PERMIT/WAIVER No. 000883 M/O1663 Longitude W 115.75835° N NAD 83/WGS 84
Issued by Water Resources Parcel No. Subdivision Name: County: Elko

3. TYPE OF WELL
 Domestic Irrigation Test Stock
 Municipal/Industrial Monitor
 Is this well being plugged because a replacement well was drilled? NO
 If yes, what is replacement well NOI?
 Is there an existing well log? YES
 If yes, what is NDWR well log #? 113118

4. EXISTING WELL CONSTRUCTION
 Depth Drilled 30 Feet Depth Cased 30 Feet

7. WELL PLUGGING PROCEDURE
 Was well cleaned out to total depth? yes no
 If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5"	PVC	SCH 40	0	20

Was the well contaminated? yes no
 Was the casing pulled? yes no
 Was the casing over drilled? yes no
 If casing was left in place, please show where additional perforations were made:

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	To	feet
FACTORY	0.03	20	feet to	30	feet
			feet to		feet
			feet to		feet
			feet to		feet
			feet to		feet

Additional Perforations:

Type of perforator used:	From	feet to	feet	Number of perms per linear foot
NONE				

5. WATER LEVEL
 Static water level 20 feet below land surface
 Artesian flow G.P.M. P.S.I.
 Water temperature <85 °F Quality

8. WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
0	feet to	30	NEAT CEMENT	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

6. Additional Notes or Comments

TREMMIE GROUT FROM BOTTOM OF WELL TO GROUND SURFACE AND REMOVED SURFACE VAULT.
 WELL NUMBER WAS MW-13

Neat Cement Fluid Weight 16 lbs/gal
 Bentonite Grout 3 % bentonite
 Date Started 4/30/2012
 Date Completed 4/30/2012

RECEIVED
 2012 JUN -1 AM 10:30
 STATE ENGINEERS OFFICE

9. DRILLER'S CERTIFICATION
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
 Name HAZ-TECH DRILLING, INC. Contractor
 Address PO BOX 940 Contractor
MERIDIAN, ID. 83680
 Nevada contractor's license number issued by the State Contractor's Board 0038018
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2246
 Signed Clayton A. Adams By driller performing actual drilling on site or contractor
 Date 5-21-12

(Rev. 12-05) USE ADDITIONAL SHEETS IF NECESSARY

40.833909°N NAD27
 115.757449°W