STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 115224
Permit No. 16593
Basin 030A

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65390

1 OWNER KINGS RIVER RANCH
MAILING ADDRESS 129 KINGS RIVER RD
OROVADA, NV. 89425

ADDRESS AT WELL LOCATION 129 KINGS RIVER RD
OROVADA, NV. 89425
Subdivision Name: D BLOCK County: HUMBOLDT

2 LOCATION NE¼ SE ¼ Sec 7 T 45 N/S R 34 E
PERMIT/WAIVER No. 16593 Issued by Water Resources Parcel No.

Latitude N 41° 47' 41.1" UTM E
Longitude W 118° 11' 15.9" N
☐ NAD 27 ☒ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?

Is there an existing well log? 72200
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION
Depth Drilled 595 Feet Depth Cased 595 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		3/16	0	402
14		1/4	400	595

Existing Perforations:
Type of perforation MILL KNIFE / SAW GLOT
Size of perforation 3/8 x 2

From	feet to	feet
395	100	
400	595	

5 WATER LEVEL
Static water level 90 feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature °F Quality

6 Additional Notes or Comments
WE USED 418 SACK OF BENTONITE CRUMBLES + 10 GALS OF POLYMER

418 BAGS BENTONITE CRUMBLES 30/50 MESH

10 GALS POLYEMER

46 BAGS CEMENT AT 7 GALS / BAG

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☐ yes ☒ no
If well was not cleaned out to total depth, please explain why: THIS WELL WAS HAD LOTS OF BREAKS WE SAW ON THE VIDEO NOT SAFE TO GO INTO

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used: MILLS KNIFE

From	feet to	feet	Number of perfs per linear foot
100	0		4

8 WELL PLUGGING MATERIALS

Material Used				
From 595 feet to 50 feet	BEN. CRUMB	☒ Pumped	☐ Poured
From feet to feet		☐ Pumped	☐ Poured
From 50 feet to 0 feet	NEAT CEMENT	☐ Pumped	☒ Poured
From feet to feet		☐ Pumped	☐ Poured
From feet to feet		☐ Pumped	☐ Poured
From feet to feet		☐ Pumped	☐ Poured

Neat Cement Fluid Weight 12.4 / 12.6 lbs/gal
Bentonite Grout 20% % bentonite
Date Started 4/13/11
Date Completed 5/15/11

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name KINGS RIVER RANCH Contractor
Address 129 KINGS RIVER RD. Contractor
OROVADA, NV. 89425
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1712
Signed Mike McDonald By driller performing actual drilling on site or contractor
Date 5/31/11

(Rev. 05-08) USE ADDITIONAL SHEETS IF NECESSARY

41.794853°N NAD27
118.186762°W