

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 115302  
Permit No. \_\_\_\_\_  
Basin 070

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66743

1. OWNER Rodney & Laurel Glinmann ADDRESS AT WELL LOCATION 7200 Pine Rd  
MAILING ADDRESS 7010 Rose Creek Rd Sonoma Ranchos #2 Winnemucca, Nv 89445  
Winnemucca, Nv 89445 Subdivision Name: 15 Uk County: Humboldt

2. LOCATION SE 1/4 NE 1/4 Sec 17 T 35N N/S R 37E E Latitude 40.911616 UTM E 429907  
PERMIT/WAIVER No. 013-233-20 Longitude 117.832294 N 4529067  
Parcel No. \_\_\_\_\_

3. WORKED PERFORMED Recondition \_\_\_\_\_  
Deepen \_\_\_\_\_ Other \_\_\_\_\_  
4. PROPOSED USE \_\_\_\_\_  
Municipal/Industrial \_\_\_\_\_ Irrigation \_\_\_\_\_ Test \_\_\_\_\_  
Monitor \_\_\_\_\_ Stock \_\_\_\_\_  
5. WELL TYPE Cable \_\_\_\_\_ RVC \_\_\_\_\_  
Air \_\_\_\_\_ Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sandy loam top soil and Gravel		0	30	30
Brown clay, silt & sand	X	30	73	43
Blue Clay	X	73	86	13
Sand	X	86	89	3
Blue Clay	X	89	102	13
Sand stratas w/ clay layers	X	102	155	53
Sand & Gravel	X	155	208	53
		208		

9. WELL CONSTRUCTION  
Depth Drilled 208 Feet Depth Cased 208  
HOLE DIAMETER (BIT SIZE)  
From \_\_\_\_\_ To \_\_\_\_\_  
10 5/8 inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
\_\_\_\_\_ inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
\_\_\_\_\_ inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/FL (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6.625</u>	<u>STEEL</u>	<u>.188</u>	<u>0</u>	<u>20</u>
<u>6.900</u>	<u>PVC</u>	<u>sdr21=.450 in</u>	<u>20</u>	<u>208</u>

Perforations:  
Type of perforation 6 inch pvc mill horizontal slot screen  
Size of perforation 1/32  
From 160 feet to 200 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal: \_\_\_\_\_  
Neat Cement \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
Cement Grout \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
Concrete Grout \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
Bentonite pellets 0 to 100 Pumped \_\_\_\_\_

Gravel Pack: \_\_\_\_\_ No 100 to 208 Pumped \_\_\_\_\_  
Type: \_\_\_\_\_ 3/8 minus  
Bentonite Chips: \_\_\_\_\_ No \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
Type: \_\_\_\_\_ Baroid Hole plug

Date started: 5/17/2012  
Date completed: 5/22/2012  
7. Water Level 58.3  
Static water level: \_\_\_\_\_ feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: COLD °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:	Bailer	Pump	Air Lift	x
	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	
<u>AIR</u>	<u>est 30</u>	<u>10</u>	<u>4</u>	

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name High Desert Drilling LLC  
Contractor  
Address 4225 E Mary Way  
Winnemucca Nevada 89445  
Nevada contractor's license number issued by the State Contractor's Board 62237  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2140 & 2364  
Signed \_\_\_\_\_  
By driller performing actual drilling of site by contractor  
Date June 15, 2012

USE ADDITIONAL SHEETS IF NECESSARY

\* See GPS in yellow highlighter above ...