STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 115326
Permit No.
Basin 137B

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER Round Mountain Gold
MAILING ADDRESS PO Box 480
Round Mountain, NV 89045

ADDRESS AT WELL LOCATION Round Mountain
D-543 (well name)

NOTICE OF INTENT NO. 33056

2. LOCATION NE ¼ SE ¼ Sec 24 T 10N N/S R 43 E
PERMIT/WAIVER No. M/O 1813 (Issued by Water Resources) Parcel No.

Latitude
Longitude
Subdivision Name:
UTM E 491966.0 ☑ NAD 27
N 4284411.00 ☐ NAD 83/WGS 84
County: Nye

3. WORKED PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other...

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other... Core

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
alluvium-sand, clay, gravel,		0	860	860
boulders				
clay-rich tuff		860	963	103
tuff-altered to clay		963	1002	39
densly welded tuff		1002	1797	795
moderately welded tuff		1797	1824	27
poorly welded tuff		1824	1860	36
peizometer set at 810' and 970'				
solid core fiberglass				
acrifical rod to set				
peizometer grout hole bottom				
to surface solid core				
casing not recovered 4.5" from				
900' to 1041'				

RECEIVED 2012 JUL -5 AM 11:2 STATE ENGINEERS OFFICE

Date started 30-May, 20 12
Date completed 16-Jun, 20 12

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1860 Feet Depth Cased 1860 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
5.5	Inches	0	Feet	120	Feet
4.5	Inches	120	Feet	1040	Feet
3.875	Inches	1040	Feet	1860	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5.5	14.4	.250	0	120
4.5	11.7	.250	120	1040
3.5	7.69	.250	1040	1860

Perforations:
Type of perforation
Size of perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 1860
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☑ No
From feet to feet

9. WATER LEVEL
Static water level 1500 feet below land surface
Artesian flow n/a G.P.M P.S.I
Water temperature n/a °F Quality n/a

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name National EWP (Contractor)
Address 580 W Silver St (Contractor)
Elko, NV 89801
Nevada contractor's license number issued by the *State Contractor's Board* 0075355
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2215
Signed (By driller performing actual drilling on site or contractor)
Date 6-29-12

(Rev. 06/10)

USE ADDITIONAL SHEETS IF NECESSARY

38.710167 °N
117.092402 °W NAD27