STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 115369
Permit No.
Basin 049

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 68913

1. OWNER ARTISAN COMMUNITIES LLC
MAILING ADDRESS 4940 LEO BINGO COURT
WASHOE VALLEY, NV 89704

ADDRESS AT WELL LOCATION 217 HAMILTON CREEK COURT
Subdivision Name: SPECIAL LANDS County: ELKO

2. LOCATION SW ¼ NW ¼ Sec 28 T 34N N/S R 55 E
PERMIT/WAIVER No. 006-09P-061
Issued by Water Resources Parcel No.

Latitude
Longitude

UTM E 11T 0601859 [X] NAD 27
N 4517699 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOP SOIL		0	2	2
SAND & GRAVEL		2	40	38
TAN CLAY		40	45	5
GREY CLAY		45	120	75
GREY SHALE		120	160	40
BLACK SAND	XXX	160	180	20

Date started: 11-Jul, 20 12
Date completed: 11-Jul, 20 12

RECEIVED 2012 JUL 18 PM 1:16 STATE ENGINEERS OFFICE

9. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	180	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	13	.188	+2	180

Perforations:
Type of perforation PLASMA CUT
Size of perforation 5/16" X 4", 7 ROWS
From 160 feet to 180 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No Will accept. L.m.J
[X] Neat Cement 4 to 15 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 50 to 180 [ ] Pumped [X] Poured
Type: 3/8" WASHED PEA GRAVEL
Bentonite Chips: [X] Yes [ ] No 15 to 50 [ ] Pumped [X] Poured
Type: 3/8" BENTONITE CHIPS

7. Water Level
Static water level: 52 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 60 °F
Quality: GOOD

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AT 160'	60		2 HOURS
AT 120'	40		

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC. (Contractor)
Address P. O. BOX 850 (Contractor)
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1408
Signed (By driller performing actual drilling on site or contractor)
Date 7/13/2012

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

HO. 805887 NAD 27
115. 792438