

**STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT**

**OFFICE USE ONLY**  
Log No. 115456  
Permit No. \_\_\_\_\_  
Basin 088

**PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 66126

1 OWNER Christine Veach ADDRESS AT WELL LOCATION 15505 Willowbrook Dr.  
MAILING ADDRESS 15505 Willowbrook Dr. Reno, NV 89511  
Reno, NV 89511 Subdivision Name: Galene Est. 1 County: Washoe

2 LOCATION SE 1/4 NW 1/4 Sec 02 T17N N/S R 19E E Latitude 39.36887 UTM E  NAD 27  
PERMIT/WAIVER No. 045-532-04 Longitude 119.82036 N  NAD 83/WGS 84

Issued by Water Resources Parcel No.

3 TYPE OF WELL  Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? No  
If yes, what is replacement well NDI? \_\_\_\_\_

Is there an existing well log? Yes  
If yes, what is NDWR well log #? 25733

4 EXISTING WELL CONSTRUCTION

Depth Drilled 175 Feet Depth Cased 175 Feet

**EXISTING CASING SCHEDULE**

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.156	0	175

7 WELL PLUGGING PROCEDURE

Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

If casing was left in place, please show where additional perforations were made:  
Additional Perforations: \_\_\_\_\_

Existing Perforations:

Type of perforation	Size of perforation	From	To
Factory saw	3/32 x 2 1/2	134	170

Type of perforator used: None

From	To	Number of perfs per linear foot

5 WATER LEVEL

Static water level 154 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	To	Material Used	Pumped	Poured
175	80	3/8" Chips	<input type="checkbox"/>	<input checked="" type="checkbox"/>
80	0	Cement	<input type="checkbox"/>	<input checked="" type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments

Well was abandoned by pouring 3/8" Bentonite Chips from 175' to 80' then pouring cement sand slurry from 80' to surface.

Neat Cement Fluid Weight \_\_\_\_\_ lbs/gal  
Bentonite Grout \_\_\_\_\_ % bentonite

Date Started 8/03/12  
Date Completed 8/03/12

RECEIVED  
2012 AUG -7 AM 10:35  
STATE ENGINEERS OFFICE

Plugs well log # 25733

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Fundin Pump & Well Service  
Address 4030 Eastlake Blvd.  
Washoe Valley, NV 89704

Nevada contractor's license number issued by the State Contractor's Board 74720  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2205

Signed Vanni Tevler  
Date 8-04-12