STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 115491
Permit No.
Basin 102

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67532

1. OWNER LOUIE SUVA CAMPOS
MAILING ADDRESS 917 DESERT BREEZE WAY
SW FERNLEY, NV 89408

ADDRESS AT WELL LOCATION 18585 CARSON HWY
FALLON, NV 89408
Subdivision Name: County: Churchill

2. LOCATION NE ¼ SW ¼ Sec 7 T 18N N/S R 26 E
PERMIT/WAIVER No. SE 006-132-37
Issued by Water Resources Parcel No.

Latitude 39°26'088"N
Longitude 119°06'409"W
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other MUD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
OVER BURDEN		0	4	4
CIBBLES AND SILTY SAND		4	36	32
GRAY CLAY		36	120	84
SILTY GRAY SANDS				
GRAY GUMMY CLAY		120	168	48
REDDISH CLAY RUSTY SANDS				
VOLCANIC GRAVELS	X	168	200	32
VOLCANIC GRAVELS	XX	200	220	20

Date started: 07-Nov, 20 2011
Date completed: 11-Nov, 20 2011

9. WELL CONSTRUCTION
Depth Drilled 220 Feet Depth Cased 220 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12 1/4	Inches	0	Feet	200	Feet
6 1/8	Inches	200	Feet	220	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.03	.188	+2	20
6 5/8 sdr	4.26	.216	20	200
5 sdr 21	3.12	.216	180	220

Perforations:
Type of perforation FACTORY SLOT
Size of perforation 3 X 3/32
From 180 feet to 220 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 0 to 50 ☐ Pumped ☒ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 50 to 220 ☐ Pumped ☒ Poured
Type: PEAT GRAVEL
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 60 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: COLD °F
Quality: GOOD

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
10	82	3 HRS

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name CAPITAL CITY WELL DRILLING AND PUMP SERVICE INC. (Contractor)
Address #20 KIT KAT DRIVE (Contractor)
CARSON CITY, NV 89706
Nevada contractor's license number issued by the State Contractor's Board 0055548
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1905
Signed (By driller performing actual drilling on site or contractor)
Date 11/11/2011

(Rev. 06-08) USE ADDITIONAL SHEETS IF NECESSARY

39.434884 °N NAD27
119.105822 °W Dec/Deg