STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 115569
Permit No.
Basin 049

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 68925

1. OWNER ARNOLD BECK CONSTRUCTION INC.
MAILING ADDRESS 247 GREENCREST DR
SPRING CREEK, NV 89815

ADDRESS AT WELL LOCATION 243 DRY CREEK TRAIL
Subdivision Name: SPECIAL LANDS County: ELKO

2. LOCATION NW ¼ SW ¼ Sec 28 T 34N N/S R 55 E
Latitude
Longitude
UTM E 11T 0601826 [X] NAD 27
N 4517303 [ ] NAD 83/WGS 84
PERMIT/WAIVER No. 006-09P-049
Issued by Water Resources
Parcel No.

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOP SOIL & GRAVEL		0	20	20
TAN CLAY & GRAVEL		20	60	40
TAN CLAY		60	80	20
BLUE GREY CLAY		80	140	60
CLAY & SOFT SANDSTONE	X	140	200	60
SOFT SANDSTONE		200	220	20

Date started: 14-Aug, 20 12
Date completed: 14-Aug, 20 12

9. WELL CONSTRUCTION
Depth Drilled 220 Feet Depth Cased 218 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 3/4	inches	0	Feet	220	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	13	.188	+2	218

Perforations:
Type of perforation PLASMA CUT
Size of perforation 3/16" X 4", 7 ROWS
From 198 feet to 218 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 4 to 25 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 55 to 218 [ ] Pumped [X] Poured
Type: 3/8" WASHED PEA GRAVEL
Bentonite Chips: [X] Yes [ ] No 25 to 55 [ ] Pumped [X] Poured
Type: 3/8" BENTONITE CHIPS

7. Water Level
Static water level: 75 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 64 °F
Quality: GOOD

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AT 215'	75		1 HOUR
AT 120'	25		1 HOUR
AT 100'	20		1 HOUR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC. (Contractor)
Address P. O. BOX 850 (Contractor)
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1166
Signed Dale C. Vieden (By driller performing actual drilling on site or contractor)
Date 8/15/2012

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

40.802324 °N
115.792894 °W NAD27

2012 AUG 20 AM 11:01 STATE ENGINEERS OFFICE