

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. **115639**
Permit No. **56449**
Basin **21a**

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. **34792**

1 OWNER **D.R. HORTON** ADDRESS AT WELL LOCATION **NA**
MAILING ADDRESS **330 CAROUSEL PARKWAY**
HENDERSON, Nev. 89014 Subdivision Name: _____ County: **CLARK**

2 LOCATION **SW 1/4 SW 1/4 Sec 33 T 22 N R 61 E** Latitude **N 35-59-05.9** UTM E NAD 27
PERMIT/WAIVER No. **56449** | **177-33-403** Longitude **W 115-10-04.7** N NAD 83/WGS 84
Issued by Water Resources: _____ Parcel No. **407**

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled? **NO**
If yes, what is replacement well NOI? _____
Is there an existing well log? **yes**
If yes, what is NDWR well log #? **38901**

4 EXISTING WELL CONSTRUCTION
Depth Drilled **505** Feet Depth Cased **505** Feet
EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	14.9	.188	+1	505

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations:
Additional Perforations:
Type of perforator used: **AIR**
From **505** feet to **50** feet Number of perfs. **6**
From _____ feet to _____ feet Number of perfs. _____
From _____ feet to _____ feet Number of perfs per line _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____

Existing Perforations:
Type of perforation **AIR ROTARY KNIFE**
Size of perforation **3/16**
From **505** feet to **50** feet
From _____ feet to _____ feet
From _____ feet to _____ feet
From _____ feet to _____ feet

5 WATER LEVEL
Static water level **19.8** feet below land surface
Artesian flow **COOL** G.P.M. _____ P.S.I. _____
Water temperature _____ °F Quality _____

8 WELL PLUGGING MATERIALS
Material Used
From **505** feet to **+1** feet **CEMENT** Pumped Poured
From _____ feet to _____ feet Pumped Poured

6 Additional Notes or Comments

DCNR/DWR RECEIVED
JUN 27 2012
LAS VEGAS OFFICE

Neat Cement Fluid Weight _____ lbs/gal
Bentonite Grout _____ % bentonite
Date Started **6-26-2012**
Date Completed **6-27-2012**

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name **VERNON H. DIMICK** Contractor
Address **HC 38 BOX 104, LV, NV, 89124** Contractor
Nevada contractor's license number issued by the State Contractor's Board **10062**
Nevada driller's license number issued by the Division of Water Resources, the on-site driller **552**
Signed **V H Dimick** By driller performing actual drilling on-site or contractor
Date **6-27-2012**

TERMS AND CONDITIONS

Payment terms for American Eagle Ready Mix, LLC, (hereafter referred to as AERM) are NET 30th of the following month. Past due accounts are subject to an annual finance charge of 18%. All returned checks are subject to a \$25 service fee and a \$50 charge may be applied for a mechanics liens placed on the property for non-payment. The Customer agrees to pay all collection costs and expenses, including attorney's fees on all past due accounts.

AERM will make reasonable efforts to deliver orders on the date and time specified and disclaims any responsibility for late delivery or insufficient quantity. In addition, the Customer expressly waives any claim of damages, right of offset or back charge as a result of a late delivery or an insufficient quantity delivered. It is noted that the Customer assumes title to the material immediately upon loading of the delivery truck.

AERM is not responsible for damage to tools, vehicles, or equipment on the job site. AERM is not responsible for damage inside the curb line. Anyone purchasing concrete (Property Owner, General Contractor, etc.) is responsible for providing safe and reasonable access to job site where the concrete is to be deposited. Washout areas must be in compliance with Clark County SWPP (Storm Water Pollution Prevention) requirements and is the responsibility of the purchaser of the material.

The Customer acknowledges and agrees that they will provide the proper concrete mix design with each order. AERM recommends all concrete poured is in compliance with Clark County Public Works IQAC (Inter Quality Assurance Committee) standards. AERM shall have no responsibility in determining the suitability of a mix design for the intended application. The Customer also agrees to unconditionally indemnify and hold harmless AERM from any and all liability cost, expense, attorney's fee or damages arising from claims based in whole or in part upon allegations that the mix design ordered by the Customer was improper or in error.

The Customer agrees to notify AERM, in writing, of any claims or defects associated with the delivery of materials within 72 hours of the first delivery. Also, the Customer must provide AERM the opportunity to correct any claim prior to incurring any cost or expense associated with the claim.

Under the State of Nevada's mechanic's lien law (NRS Chapter 108), any contractor, laborer, material supplier or other person who helps improve the property but is not paid, has a right to enforce a claim against said property by filing a mechanic's lien. After a Mechanic's Lien has been filed, the property may be sold by a court officer and the proceeds of the sale used to satisfy the mechanic's lien. This will happen even if the original contractor was paid in full. All subcontractors, laborers and material suppliers must be paid and a release must be obtained from each to insure a Mechanic's Lien will not be placed on the property.

WARNING: Exposure of sufficient duration to wet ready mix (Concrete) can cause serious, potentially irreversible tissue (skin or eye) destruction in the form of chemical (caustic) burns.