STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116015
Permit No.
Basin 137B

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69240

1. OWNER Round Mountain Gold Corp. RMW-2
MAILING ADDRESS P.O. Box 480
Round Mountain, NV. 89045

ADDRESS AT WELL LOCATION South Rib II
Subdivision Name: County: Nye

2. LOCATION SW¼SE¼ Sec02T09N/ R43E
PERMIT/WAIVER NO. NEV2012102 Issued by Water Resources Parcel. No.

Latitude Longitude
UTM E 489758 N 4279177 ☒ NAD 27 ☐ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	453	453
Neat Cement		0	20	20
Hole Plug		20	337	317
Silica Sand		337	372	35
Hole Plug		372	377	5
Silica Sand		377	453	76

Date started: October 27, 20 12
Date completed: November 10, 20 12

9. WELL CONSTRUCTION
Depth Drilled 453 Feet Depth Cased 449 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
14.75 Inches	0 Feet	20 Feet
9.875 Inches	20 Feet	453 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	17.02	.250	+3	5
4.5	286	.337	+1	449

Perforations:
Type of perforation Slotted
Size of perforation .020
From 339 feet to 369 feet
From 379 feet to 449 feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 20 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 337 to 372 ☒ Pumped ☐ Poured
Type: #8 Silica Sand
Bentonite Chips: ☒ Yes ☐ No 20 to 337 ☒ Pumped ☐ Poured
Type: 3/8" Hole Plug

7. Water Level
Static water level: 378 feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I
Water Temperature: Cool °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Air Lift	5		
	38.	662975°N	NAD27
	117.	117685°W	

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Boart Longyear (CONTRACTOR)
Address 2745 California Ave. (CONTRACTOR)
SLC., UT. 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2258
Signed
By driller performing actual drilling on site or contractor
Date November 13, 2012