

ORIGINAL

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 116062
Permit No.
Basin 07D

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69939

1 OWNER CYANCO ADDRESS AT WELL LOCATION CYANCO PLANT
MAILING ADDRESS 5505 Cyanco Drive Winnemucca, NV 89445
Subdivision Name: Winnemucca County: Humboldt

2 LOCATION SW 1/4 NE 8E 1/4 Sec 6 T 35N N/S/R 37 E Latitude 40° 56.401 N UTM E NAD 27
PERMIT/WAIVER No. 54244 & 54245 Longitude 117° 51.600 W N NAD 83/WGS 84

3 TYPE OF WELL
Domestic Irrigation Test
Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled? NO
Is there an existing well log? YES
If yes, what is NDWR well log #? 34305

4 EXISTING WELL CONSTRUCTION
Depth Drilled 183' Feet Depth Cased 183' Feet
EXISTING CASING SCHEDULE
Size O.D. (Inches) Weight/Ft. (Pounds) Wall Thickness (Inches) From (Feet) To (Feet)
20" .312" 0' 60'
12" .312" +2' 183'

Existing Perforations:
Type of perforation SCREEN
Size of perforation 0.040"
From 63' feet to 183' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: N/A
From feet to feet Number of perms per linear foot
From feet to feet Number of perms per linear foot
From feet to feet Number of perms per linear foot
From feet to feet Number of perms per linear foot
From feet to feet Number of perms per linear foot
From feet to feet Number of perms per linear foot

5 WATER LEVEL
Static water level 58' feet below land surface
Artesian flow NO G.P.M. 0 P.S.I.
Water temperature COOL °F Quality

8 WELL PLUGGING MATERIALS
Material Used
From 0' feet to 20' feet NEAT CEMENT Pumped Poured
From 20' feet to 183' feet BENTONITE GROUT Pumped Poured
From feet to feet Pumped Poured

6 Additional Notes or Comments
Plugs Well Log No. 34305

Neat Cement Fluid Weight 15 LBS lbs/gal
Bentonite Grout 30% % bentonite
Date Started 12/5/2012
Date Completed 12/6/2012

RECEIVED
2013 JAN - 7 AM 11:11
STATE ENGINEERS OFFICE

NAD 27
40.940113° N
117.859033° W

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources - West, Inc. Contractor
Address 4975 W. Winnemucca Blvd. Contractor
Winnemucca, NV 89445
Nevada contractor's license number issued by the State Contractor's Board 56797
Nevada driller's license number issued by the Division of Water Resources, the on-site driller #2177
Signed Michelle Strother
By driller performing actual drilling on site or contractor
Date 1/4/2013