STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116151
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 35989

1. OWNER County of Clark (Administrative)
MAILING ADDRESS 500 S. Grand Pkwy
Las Vegas, NV 89155

ADDRESS AT WELL LOCATION 300 S Casino Center Blvd
Subdivision Name: Correction Center County: Clark

2. LOCATION SE ¼ NW ¼ Sec 34 T 20S N/S R 61 E
PERMIT/WAIVER No DW-1327 13934210033
Issued by Water Resources Parcel No.

Latitude 36 10'04.76"N UTM E ☐ NAD 27
Longitude 115 08'47.64"W N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
DW # 1				
				#####

DCNR/DWR
RECEIVED
JAN 09 2013
LAS VEGAS OFFICE

Date started 2-Oct , 20 12
Date completed 2-Oct , 20 12

7. Water Level
Static water level: 15 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 35 Feet Depth Cased 35 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
24	Inches	0	Feet	35	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	6	3/8	0	35

Perforations:
Type of perforation machine slot
Size of perforation 0.032
From 15 feet to 35 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☒ ≥30% Bentonite Grout 10 to 12 ☐ Pumped ☒ Poured
Gravel Pack: ☒ Yes ☐ No 12 to 35 ☐ Pumped ☒ Poured
Type: 3/8 Pea Gravel
Bentonite Chips: ☒ Yes ☐ No 10 to 12 ☐ Pumped ☒ Poured
Type: 3/8's

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Viking Drillers Inc
Contractor
Address 801 Northport Dr.
Contractor
West Sacramento, CA
Nevada contractor's license number issued by the State Contractor's Board 0034680
Nevada driller's license number issued by the Division of Water Resources, the on-site driller Dew-2361
Signed
By driller performing actual drilling on site or contractor
Date 1/7/2013

(Rev.05-08)

USE ADDITIONAL SHEETS IF NECESSARY

36.168018 -NAD 27
-115.145733

THIS BORING LOG IS FOR VIKING'S INTERI... PURPOSES ONLY. IT DOES NOT REPRESENT INFORMATION PROVIDED BY A SOILS ENGINEER.

LOG FOR BORING NO. 1		JOB NAME: Bombard			
DATE STARTED 10-2-10	DATE COMPLETED	LOGGED BY Ed	DRILLED BY Ed	TYPE OF DRILL RIG #32	JOB NO. 6102
DEPTH OF HOLE 35'	DIAMETER OF HOLE 24"	CASING 8"	PERFORATIONS 20'	SAMPLING METHOD	ELEVATION

LOCATION: see Back

DRILLERS NOTES: used a 30" X 20' starter
No spacers used due to gravel in Excavation
Rock Tools Needed

DEPTH	SAMPLES	GRAPHIC	DESCRIPTION
0'			Base rock
			Bird eye gravel
10'		static in casing	Green packed silt clay
20'			hard Cleechi
			Light Cleechi (Breaking up easy)
30'			
40'			
50'			
60'			
70'			
80'			
90'			
100'			

DCNR/DWR
RECEIVED
JAN 09 2013
LAS VEGAS OFFICE
OCT 05 2012