STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116193
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36815

1. OWNER Ewing Rex C Jr, Ewing Bros Inc, Ewing Bros Auto Body
MAILING ADDRESS 1200 N. A St., Las Vegas, NV 89106
ADDRESS AT WELL LOCATION 1300 A St.
Subdivision Name: County: Clark

2. LOCATION NW ¼ NE ¼ Sec 27 T 20 N/S R 61 E
PERMIT/WAIVER No. 139-27-501-007
Issued by Water Resources Parcel No.
Latitude 36.18517 UTM E ☐ NAD 27
Longitude 115.14160 N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill		0	4	4'
Clayey sand w/gravel		4	8	4'
Sandy Clay, Brown		8	10	2'
Sandy Clay, part cemented		10	11	1'
Sandy Clay		11	12	1'
Silty sand, Lt Brown		12	14	2'
Clayey sand		14	17	3'
Sandy Clay		17	19	2'
Silty Clay		19	25	6'
Sandy Clay, v. Moist		25	27	2'

Date started: 9/5 , 20 12
Date completed: 9/5 , 20 12

7. Water Level
Static water level: feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

DCNR/DWR
RECEIVED
NOV 06 2012

9. WELL CONSTRUCTION
Depth Drilled 27 Feet Depth Cased 27 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	27 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	PVC	Sch 40	0	22

Perforations:
Type of perforation Factory
Size of perforation .020
From 22 feet to 27 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 0 to 15 ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack ☒ Yes ☐ No 21.5 to 27 ☐ Pumped ☒ Poured
Type: #12
Bentonite Chips: ☒ Yes ☐ No 15 to 21.5 ☐ Pumped ☒ Poured
Type: Hole plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge
Name Elite Drilling Inc. Contractor
Address PO Box 96565 Contractor
Las Vegas, NV 89193-6565
Nevada contractor's license number issued by the State Contractor's Board 0054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller NA-1869
Signed [signature]
By driller performing actual drilling on-site or contractor
Date 10/15/12

RECEIVED
OCT 23 2012
FLAMINGO

USE ADDITIONAL SHEETS IF NECESSARY

36.185200 – NAD 27
– 115.140765

INSPO 3-08

LAS VEGAS OFFICE

(O) 627