STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 1161960
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36075
WELL NAME (if applicable): MW-3

1. OWNER/CLIENT NAME Constantino Noval Nevada 2 LLC
MAILING ADDRESS 2500 W Sahara Ave #211
Las Vegas, Nevada 89102

DETAILED ADDRESS AT WELL LOCATION 5001 E Bonanza Road
Las Vegas, Nevada 89102
Subdivision Name: County: Clark

2. PLS LOCATION NE ¼ NE ¼ 32 Sec 20S N/S 62 E
PERMIT/WAIVER NO. 140-32-502-003
Issued by Water Resources Current Permit No

Latitude 36.172312 UTM E -115.064156 ☒ NAD 27
Longitude UTM N ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Fill-Silty Gravel			0	4	6
CL-Sandy Clay			4	7	3
ML-Clayey Silt			7	13	6
CL-Lean Clay			13	18	5
SM-Silty Sand		X	18	23	5
GC-Clayey Gravel			23	25	2
CL-Sandy Clay			25	34	9

DCNR/DWR
RECEIVED
DEC 1 0 2012
LAS VEGAS OFFICE

Date started: 30-Oct , 20 12
Date completed: 12/11/12 , 20

9. WELL CONSTRUCTION
Depth Drilled: 34 Feet Depth Cased: 34 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	34	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	Sch-40	PVC	0	19

PERFORATIONS:
Type of perforation: 2" OD Factory Slotted Schedule 40 PVC
Size of perforation: 0.02
From 19 Feet To 34 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☐ Sanitary Seal		to		☐ Pumped	☐ Poured
☐ Neat Cement		to		☐ Pumped	☐ Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☒ Concrete Grout	0	to	1	☐ Pumped	☒ Poured
☒ Bentonite Chips	1	to	18	☐ Pumped	☒ Poured
☐ Bentonite Grout		to		☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:					
☐ Gravel Pack [> 0.2 in.]		to		☐ Pumped	☐ Poured
☒ Sand Pack [< 0.2 in.]	18	to	34	☐ Pumped	☒ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

7. WATER QUALITIES
Static water level: 21.93 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National EWP
Contractor
Address 152 Laguna Landing Dr, Henderson, NV 89002
Contractor
Nevada contractor's license number as issued by the State Contractor's Board: 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) 2057
Signed: [signature]
Driller performing actual drilling on site or contractor
Date: 12/11/12

(Rev. 06-12)
USE ADDITIONAL SHEETS IF NECESSARY