STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116233
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36960
WELL NAME (if applicable): OMW-71A

1. OWNER/CLIENT NAME Rose Peline Avis Budget Car Rental (Clark County)
MAILING ADDRESS 6 Sylvan Wy Parsippany NJ 07054

DETAILED ADDRESS AT WELL LOCATION 450' S. of Tropicana 40' W of Curb on Maryland Parkway
Subdivision Name: County: Clark

2. PLS LOCATION NE ¼ NE ¼ 26 Sec. 21 N(S) 61 E
PERMIT/WAIVER NO. 162-27-599-003
issued by Water Resources Current Parcel No

Latitude 36°06'00.11"N UTM E ☐ NAD 27
Longitude 115°08'12.88"W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☒ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Asphalt			0	1	1
Gravely Sand/Base			1	5	4
Calliche			5	7	2
Silty Gravely Sand			7	8.5	2
Lhgt brn grvl,silty, trc snd			8.5	11.7	3
Cleysilt lght brn			11.7	12	0
cley silt lght brn moist			12	16	4
Tan clayey silt slighly mst			16	19	3
lght brn clay			19	22.5	4
sandy cley gravel lght brn			22.5	28.5	6
lght brn clayey gravel san			28.5	32.5	4
brn clay sand gravel			32.5	45	13
clayeyslt grvl brn			45	52	7
clayey sandy silt brn			52	62.5	11

DCNR/DWR
RECEIVED
DEC 06 2012
LAS VEGAS OFFICE

Date started: 16-Oct, 20 12
Date completed: 17-Oct, 20 12

7. WATER QUALITIES
Static water level: 0 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality: ND

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled: 60' Feet Depth Cased: 60' Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6 5/5	Inches	0	Feet	62.5	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	55

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.02
From 55 Feet To 60 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☒ Sanitary Seal	52' to 57'			
☒ Neat Cement	3' to 52'		☒ Pumped	☐ Poured
☐ Cement Grout	to		☐ Pumped	☐ Poured
☒ Concrete Grout	0.5' to 3'		☐ Pumped	☒ Poured
☐ Bentonite Chips	to		☐ Pumped	☐ Poured
☐ Bentonite Grout	to		☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:				
☒ Gravel Pack [> 0.2 in.]	57 to 62.5		☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]	to		☐ Pumped	☐ Poured
☐ Other, explain:	to		☐ Pumped	☐ Poured

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National Exploration Wells & Pumps (Contractor)
Address 5566 ArrowHighway, Montclair CA 91763 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2111-T1
Signed: (By driller performing actual drilling on site or contractor)
Date: 11/29/2012

(Rev. 08-12) USE ADDITIONAL SHEETS IF NECESSARY

36.100058 - NAD 27
-115.136080