

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 116252  
Permit No. 81279  
Basin 02B

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 70215

1 OWNER HYCROFT RESOURCES & DEVELOPMENT INC.  
MAILING ADDRESS PO BOX 3030 WINNEMUCCA, NV  
89445

ADDRESS AT WELL LOCATION HYCROFT MINE  
LEWIS WELL #1

2 LOCATION SE 1/4 SE 1/4 Sec 17 T 35N N/S R 30 E  
PERMIT/WAIVER No. 81279  
Issued by Water Resources Parcel No.

Subdivision Name: \_\_\_\_\_ County: Humboldt  
Latitude 40° 53.973 N UTM E  NAD 27  
Longitude 118° 38.310 W N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? YES  
If yes, what is replacement well NOI? 69933

Is there an existing well log? YES  
If yes, what is NDWR well log #? 116047  
N/A

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 400' Feet Depth Cased 385' Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10 3/4"		.250" HSLA	+2'	385'

If well was not cleaned out to total depth, please explain why: \_\_\_\_\_  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

Existing Perforations:

Type of perforation	Size of perforation	From	To
LOUVERED & MILL SLOT	0.050" & 1/4" X 1"	120'	385'

Additional Perforations:

Type of perforator used:	From	To	Number of perfs per linear foot
HOLTE AIR PERFORATOR	100'	120'	6 Rows

5 WATER LEVEL  
Static water level 135.75' feet below land surface  
Artesian flow NO G.P.M. 0 P.S.I.  
Water temperature COOL °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	To	Material Used	Applied	Notes
0'	20'	NEAT CEMENT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured	
20'	385'	BENTONITE GROUT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured	
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured	
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured	
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured	
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured	

6 Additional Notes or Comments

Plug Well Log No. 116047  
Replacement Well drilled  
under NO 1 69933 Well  
Log No. 116048

STATE ENGINEERS OF NEVADA  
SUPERVISOR  
NAD 27  
40.899647°N  
118.637508°W

Neat Cement Fluid Weight 15 LBS lbs/gal  
Bentonite Grout 30% % bentonite  
Date Started 1/26/2013  
Date Completed 1/28/2013

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Hydro Resources - West, Inc. Contractor  
Address 4975 W. Winnemucca Blvd. Contractor  
Winnemucca, NV 89445  
Nevada contractor's license number issued by the State Contractor's Board 56797  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller # 2483

Signed Michelle Strother  
By driller performing actual drilling on site or contractor  
Date 1/31/2013